

Continued from previous page

Capacity (ml)	Thread	Ø ext. (mm)	Height (mm)	Material	Neck I-Ø (mm)	Pk	Cat. No.
2000	38-430	121	249	LDPE/PP	25	1	215-7742
2000	38-430	121	249	PPCO	25	1	215-7752
4000	38-430	152	333	LDPE/PP	25	1	215-7744
4000	38-430	152	333	PPCO	25	1	215-7754
8000	53B	193	409	LDPE/PP	37	1	215-7748
8000	53B	196	409	PPCO	37	1	215-7758



Bottles, narrow mouth, with screw cap, Nalgene®
Thermo Scientific



PPCO, translucent with PP screw cap

Ideal for storing and shipping liquids.

- Very good chemical resistance
- Heat resistant up to +121 °C, autoclavable with or without contents
- Robust, leakproof

Capacity (ml)	Thread (mm)	Ø ext. (mm)	Height (mm)	Neck I-Ø (mm)	Pk	Cat. No.
4	13	16	41	8	12	215-7561
8	20	25	45	14	12	215-7562
15	20	25	58	14	12	215-7563
30	20	34	61	14	12	215-7564
60	20	37	85	14	12	215-7565
125	24	50	101	18	12	215-7566
250	24	61	133	18	12	215-7568
500	28	73	170	21	12	215-7570
1000	38-430	91	216	27	6	215-7571



Bottles, narrow mouth, with screw caps, Azlon®
SciLabware



PP, translucent with PP screw cap

Ideal for liquid storage, media preparation and sampling applications.

- Very good chemical resistance
- Autoclavable
- Robust, leakproof

Capacity (ml)	Ø ext. (mm)	Height (mm)	Neck I-Ø (mm)	Pk	Cat. No.
60	40	79	17	10	215-0528
125	50	103	17	10	215-0529
150	50	116	22	10	215-3109
250	60	140	22	10	215-0530
500	75	160	22	10	215-0531
1000	90	200	22	5	215-0532
2000	120	237	34	5	215-0533