

Bottles, narrow mouth, with screw cap, boston type, Nalgene® Thermo Scientific



HDPE, translucent with PP screw cap

Ideal for storing, packaging and transporting liquids. Robust, strong and stable.

- Good chemical resistance
- Heat resistant from -100 to +120 °C
- Leakproof

Capacity (ml)	Thread	Ø ext. (mm)	Height (mm)	Neck I-Ø (mm)	Pk	Cat. No.
4	13-415	16	41	8	2.000	215-0246
8	20-415	25	45	14	2.000	215-1379
15	20-415	25	58	14	2.000	215-0234
30	20-415	34	61	14	1.000	215-0189
60	20-415	37	85	14	1.000	215-0190
125	24-415	50	101	18	500	215-0194
175	24-415	54	125	18	250	215-0207
250	24-415	61	133	18	250	215-0209
500	28-415	73	170	21	125	215-1377
1000	38-430	91	216	27	50	215-0225

Bottles, narrow mouth, low particulate, IP2, with screw cap, Nalgene® Thermo Scientific



HDPE, translucent with PP screw cap

Bottles with an average of less than 30 particles per ml at 0,3 µm and greater. Excellent for storing high-purity chemicals. Product includes a certificate of quality that assures the product has been tested and accepted in accordance with Nalgene® specifications. Low particulate IP2 bottles can be used in compliance with the regulations for customers who are designing, assembling and certifying their own combination packaging.

- Good chemical resistance
- Screw cap supplied assembled on the bottle
- Leakproof

Capacity (ml)	Thread (mm)	Ø ext. (mm)	Height (mm)	Neck I-Ø (mm)	Pk	Cat. No.
125	24	51	101	18	12	215-1269
250	24	61	133	18	12	215-1271
500	28	73	171	21	12	215-1272
1000	38-430	91	216	27	6	215-1279

Bottles, narrow mouth, with screw cap, Azlon® SciLabware



HDPE, translucent with PP screw cap

Ideal for storing a wide range of liquids.

- Excellent general chemical resistance
- Heat resistance from -100 to +120 °C
- Lightweight but very durable in use

Capacity (ml)	Ø ext. (mm)	Height (mm)	Neck I-Ø (mm)	Pk	Cat. No.
30	32	66	17	10	215-3359
100	50	89	22	10	215-3360
125	50	102	22	10	215-3100
150	50	116	22	10	215-3104
250	60	140	22	10	215-3105
500	75	160	22	10	215-3107