

Clamps, three pronged





Laboral aluminium alloy

- Clamping prongs covered in vinyl to protect clamped items
- With two easy action knurled screws for adjusting the clamping fingers independently of each other

Spanning width (mm)	Pk	Cat. No.
12 - 100	5	241-0019



SELECTED FOR YOU

Clamps, four pronged



Stainless steel

- Robust design, clamp rod diameter 12 mm, 140 mm long
- With two easy action knurled screws for adjusting the clamping fingers independently of each other

Spanning width (mm)	Pk	Cat. No.
35 - 100	2	241-0029

Clamps, three pronged Usbeck



Zinc die-cast, powder coated

- The prongs of the clamps are covered with a plastic coating to protect the items clamped
- Without bosshead for fixing to stand
- With wing screws for rapid easy fixing

Spanning width (mm)	For	Pk	Cat. No.
0 - 40	rod Ø 8 mm	1	241-7431
0 - 40	rod Ø 10 mm	1	241-7432
25 - 80	rod Ø 10 mm	1	241-7433

Clamps, three pronged Bochem



Aluminium

- The fingers of the clamps are covered with a plastic coating to protect the items clamped
- Without bosshead for fixing to stand
- With T-screws screws for rapid easy fixing

Spanning width (mm)	Pk	Cat. No.
0 - 70	1	241-3156

Clamps, three pronged



Aluminium die-cast clamps with three rubber covered jaws and nickel plated screws.

Description	Spanning width (mm)	Pk	Cat. No.
Clamps, three pronged	70	1	212-9500

