

Mixing measuring cylinders
Hirschmann Laborgeräte



DURAN®, borosilicate glass, with PE stopper, class B

- Calibrated to contain 'In'
- Hexagonal glass base, NS ground socket
- Main point graduations, blue graduations

DIN EN ISO 4788

Capacity (ml)	Division (ml)	Height (mm)	NS	Pk	Cat. No.
10	0,2	160	10/19	2	612-3080
25	0,5	183	14/23	2	612-3081
50	1	226	19/26	2	612-3082
100	1	290	24/29	2	612-3083
250	2	367	29/32	2	612-3084
500	5	425	34/35	2	612-3085
1000	10	510	45/40	1	612-3086
2000	20	610	45/40	1	612-3087



Measuring cylinders



Borosilicate glass 3.3, tall form, class A

- Calibrated to contain (TC, In)
- Hexagonal glass base, with spout
- Blue graduations with ring marks at major graduations
- Certificate of conformity with batch number

DIN 12680

Capacity (ml)	Division (ml)	Tolerance (± ml)	Pk	Cat. No.
5	0,1	0,05	2	612-3832
10	0,2	0,1	2	612-3833
25	0,5	0,25	2	612-3834
50	1	0,5	2	612-3835
100	1	0,5	2	612-3836
250	2	1	2	612-3837
500	5	2,5	2	612-3838
1000	10	5	1	612-3839
2000	20	10	1	612-3840

Measuring cylinders, BLAUBRAND® ETERNA
Brand



Borosilicate glass 3.3, tall form, class A, conformity certified

- Calibrated to contain (TC, In)
- Hexagonal glass base, with spout
- Ring marks at major graduations, marks and inscriptions in ETERNA amber stain

DIN EN ISO 4788

Ordering information: Supplied with a batch certificate. Measuring cylinders are also available on request with an individual certificate, a USP individual certificate or a DAkkS calibration certificate.

Capacity (ml)	Division (ml)	Tolerance (± ml)	Height (mm)	Pk	Cat. No.
5	0,1	0,05	115	2	612-5030
10	0,2	0,1	140	2	612-5031
25	0,5	0,25	170	2	612-5032
50	1	0,5	200	2	612-5033
100	1	0,5	260	2	612-5034
250	2	1	335	2	612-5035
500	5	2,5	365	2	612-5036
1000	10	5	465	1	612-5037
2000	20	10	505	1	612-9268