

Dropping funnels, cylindrical, without pressure balance Lenz



DURAN®, borosilicate glass, with glass key

Standard ground joint cone and socket. With divisions. Stopcock with thread guard.

- Very good chemical resistance
- High temperature resistance
- Minimal thermal expansion giving relatively high resistance to temperature changes

| Capacity (ml) | Cone size (NS) | Socket size (NS) | Division (ml) | Pk | Cat. No. |
|---------------|----------------|------------------|---------------|----|----------|
| 50 | 14/23 | 14/23 | 1 | 1 | 271-5102 |
| 50 | 29/32 | 29/32 | 1 | 1 | 271-5112 |
| 100 | 14/23 | 14/23 | 2 | 1 | 271-5103 |
| 100 | 29/32 | 29/32 | 2 | 1 | 271-5113 |
| 250 | 29/32 | 29/32 | 5 | 1 | 271-5114 |
| 500 | 29/32 | 29/32 | 10 | 1 | 271-5115 |
| 1000 | 29/32 | 29/32 | 20 | 1 | 271-5116 |



Dropping funnels, cylindrical, without pressure balance Lenz



DURAN®, borosilicate glass, with PTFE key

Cylindrical shape. With standard ground joint cone and socket. Clearly visible white divisions for approximate volume reading.

- Very good chemical resistance
- High temperature resistance
- Minimal thermal expansion giving relatively high resistance to temperature changes

DIN ISO 4800

| Capacity (ml) | Cone size (NS) | Socket size (NS) | Division (ml) | Pk | Cat. No. |
|---------------|----------------|------------------|---------------|----|----------|
| 50 | 14/23 | 14/23 | 1 | 1 | 201-1124 |
| 50 | 29/32 | 29/32 | 1 | 1 | 201-1125 |
| 100 | 14/23 | 14/23 | 2 | 1 | 271-5123 |
| 100 | 29/32 | 29/32 | 2 | 1 | 201-1126 |
| 250 | 29/32 | 29/32 | 5 | 1 | 201-1127 |
| 500 | 29/32 | 29/32 | 10 | 1 | 201-1128 |
| 1000 | 29/32 | 29/32 | 20 | 1 | 201-1129 |



Dropping funnels, cylindrical, with pressure balance Lenz



DURAN®, borosilicate glass, clear, with glass key

Standard ground joint cone and socket, with divisions for approximate volume reading. Stopcock with thread guard.

- Very good chemical resistance
- High temperature resistance
- Minimal thermal expansion giving relatively high resistance to temperature changes

| Capacity (ml) | Cone size (NS) | Socket size (NS) | Division (ml) | Pk | Cat. No. |
|---------------|----------------|------------------|---------------|----|----------|
| 50 | 14/23 | 14/23 | 1 | 1 | 271-5152 |
| 50 | 29/32 | 29/32 | 1 | 1 | 271-5162 |
| 100 | 14/23 | 14/23 | 2 | 1 | 271-5153 |
| 100 | 29/32 | 29/32 | 2 | 1 | 271-5163 |
| 250 | 29/32 | 29/32 | 5 | 1 | 271-5164 |
| 500 | 29/32 | 29/32 | 10 | 1 | 271-5165 |
| 1000 | 29/32 | 29/32 | 20 | 1 | 271-5166 |