

Continued from previous page

Gauge	Volume (ml)	Length (mm)	Ø ext. (mm)	Type	Type of tip	Pk	Cat. No.
-	1	-	-	1001 LT	-	1	549-1189
-	1	-	-	1001 TLL *	-	1	613-1321
-	1	-	-	1001 TLL	-	1	549-0231
-	1,25	-	-	1001,25 LT	-	1	549-0250
-	2,5	-	-	1002 LT	-	1	549-1192
-	2,5	-	-	1002 TLL *	-	1	613-1322
-	5	-	-	1005 LT	-	1	549-1194
-	5	-	-	1005 TLL *	-	1	613-1323
-	10	-	-	1010 LT	-	1	549-1196
-	10	-	-	1010 TLL *	-	1	613-1324
22	1	51	0,72	1001 RN	2	1	549-0369
22	1	51	0,72	1001 LTN	2	1	549-1190
22	1	51	0,72	1001 LTN	3	1	613-1300
22	1	51	0,72	1001 LTN	5	1	549-1191
22	2,5	51	0,72	1002 RN	2	1	549-1265
22	2,5	51	0,72	1002 LTN	2	1	613-1302
22	2,5	51	0,72	1002 LTN	3	1	549-0370
22	5	51	0,72	1005 RN	2	1	549-1266
22	5	51	0,72	1005 LTN	2	1	613-1303
22	5	51	0,72	1005 LTN	5	1	549-1195
22	10	51	0,72	1010 RN	2	1	549-1267
22	10	51	0,72	1010 LTN	2	1	549-0232

\* without slots

## 1700 series Gastight® syringes Hamilton



Gas-tight syringes for use with gases or liquids.

- PTFE plunger tip creates a leak-free seal
- Syringe glass barrel and plunger are interchangeable

Gauge	Volume (µl)	Length (mm)	Ø ext. (mm)	Type	Type of tip	Pk	Cat. No.
-	10	-	-	1701 LT	-	1	549-1125
-	25	-	-	1702 LT	-	1	549-1131
-	50	-	-	1705 LT	-	1	549-1170
-	50	-	-	1705 TLL **	-	1	613-0496
-	50	-	-	1705 TLLX *	-	1	613-1421
-	100	-	-	1710 LT	-	1	549-1175
-	100	-	-	1710 TLL **	-	1	549-0365
-	100	-	-	1710 TLLX *	-	1	613-1422
-	250	-	-	1725 LT	-	1	549-1180
-	250	-	-	1725 TLL **	-	1	549-0367
-	250	-	-	1725 TLLX *	-	1	613-1423
-	500	-	-	1750 LT	-	1	549-1184
-	500	-	-	1750 TLL **	-	1	613-1425
-	500	-	-	1750 TLLX *	-	1	613-1424
26s	10	51	0,47	1701 RN	2	1	549-1126
26s	10	51	0,47	1701 N	2	1	549-1124
26s	10	51	0,47	1701 N	3	1	549-0220
22s	25	51	0,72	1702 RN	2	1	549-1132
22s	25	51	0,72	1702 N	2	1	549-1130
22s	50	51	0,72	1705 RN	2	1	549-1171
22s	50	51	0,72	1705 N	2	1	549-1169
22s	100	51	0,72	1710 RN	2	1	549-1176
22s	100	51	0,72	1710 N	2	1	549-1174
22s	250	51	0,72	1725 RN	2	1	549-1181
22s	250	51	0,72	1725 N	2	1	549-1179
22s	250	51	0,72	1725 N	3	1	549-1183
22	500	51	0,72	1750 RN	2	1	549-1187
22	500	51	0,72	1750 N	2	1	549-1186

\* for Microlab®

\*\* without slots