

Continued from previous page

Ø int. (mm)	Ø ext. (mm)	Wall thickness (mm)	Pk	Cat. No.
0,80	2,40	0,80	15 m	228-1278
1,60	3,20	0,80	15 m	228-1279
1,60	4,80	1,60	15 m	228-1280
2,40	4,00	0,80	15 m	228-1281
2,40	5,60	1,60	15 m	228-1282
3,20	4,80	0,80	15 m	228-1283
3,20	6,40	1,60	15 m	228-1284
4,00	5,60	0,80	15 m	228-1285
4,00	7,20	1,60	15 m	228-1286
4,80	6,40	0,80	15 m	228-1287
4,80	8,00	1,60	15 m	228-1288
4,80	9,60	2,40	15 m	228-1289
6,40	8,00	0,80	15 m	228-1290
6,40	9,60	1,60	15 m	228-1263
6,40	11,20	2,40	15 m	228-1291
6,40	12,80	3,20	15 m	228-1292
7,90	11,10	1,60	15 m	228-1293
7,90	12,70	2,40	15 m	228-1294
9,50	12,70	1,60	15 m	228-1265
9,50	14,30	2,40	15 m	228-1295
9,50	15,90	3,20	15 m	228-1296
11,10	14,30	1,60	15 m	228-1297
11,10	15,90	2,40	15 m	228-1298
12,70	15,90	1,60	15 m	228-1299
12,70	17,50	2,40	15 m	228-1310
12,70	19,10	3,20	15 m	228-1267
14,30	19,10	2,40	15 m	228-1311
15,90	20,70	2,40	15 m	228-1312
15,90	22,30	3,20	15 m	228-1313
19,10	25,40	3,20	15 m	228-1314
22,20	28,60	3,20	15 m	228-1315
25,40	31,80	3,20	15 m	228-1316
25,40	35,00	4,80	15 m	228-1317
31,80	38,20	3,20	15 m	228-1318

Pump tubing, Tygon® S3™ E-LFL Saint-Gobain



Non DEHP and phthalate-free tubing

Longest flexible life of any clear Tygon® tubing. The non ageing and broad chemical resistance properties enable users to utilise the tubing for transferring chemicals, cleaning agents and bactericides without danger of corrosion (as with metals) or oxidation (as with rubber). Tygon® S3™ E-LFL tubing is formulated specifically for use in peristaltic pump applications.

- Over 1000 hours pump tubing life at 0 psi; over 600 hours pump tubing life at 10 psi
- Extremely low particle spallation
- Contains no BPA or phthalates
- Broad chemical resistance
- Meets USP Class VI, ISO 10993 and FDA criteria - suitable for pharma, medical and food applications

Temperature resistant from -55 to +74 °C

Hardness (Shore durometer A): 56

Density: 1,17

Ø int. (mm)	Ø ext. (mm)	Wall thickness (mm)	Pk	Cat. No.
1,60	4,80	1,60	7,5 m	228-1258
3,20	6,40	1,60	7,5 m	228-1259
4,80	7,90	1,60	7,5 m	228-1260
6,40	9,50	1,60	7,5 m	228-1261
6,40	12,80	3,20	7,5 m	228-1321
7,90	11,20	1,60	7,5 m	228-1262
9,50	15,90	3,20	7,5 m	228-1322
12,70	19,10	3,20	7,5 m	228-1323
19,00	31,75	6,40	3 m	228-1319
25,40	34,90	4,80	3 m	228-1320