



## Test tubes without rim, heavy wall



### Borosilicate glass, grade 3.3, SAMCO '33'

Borosilicate test tubes are suitable for all usual laboratory applications. They will withstand temperature change up to and including boiling of samples. They are also highly chemically resistant. Manufactured to the dimensions, tolerances and quality requirements of ISO 4142:2002, to meet all applications for re-usable glass tubes. Thick walled.

- Very good chemical resistance
- High temperature resistance
- Minimal thermal expansion, giving relatively high resistance to temperature changes

Length (mm)	Ø ext. (mm)	Pk	Cat. No.
75	10	100	212-7039
75	12	100	212-7040
100	12	100	212-7041
125	16	100	212-7042
150	16	100	212-0463
150	18	100	212-7043
150	24	50	212-7044

## Specimen tubes



### Soda-lime glass

Straight sided tubes, with beaded rim and push in PE closure.

Length (mm)	Ø ext. (mm)	Wall thickness (mm)	Pk	Cat. No.
38	10	0,60	250	212-7109
38	12	0,85	100	212-0566
50	10	0,60	250	212-7045
50	12	0,85	100	212-7046
50	16	0,85	100	212-0569
50	19	0,85	100	212-7047
50	25	0,85	100	212-7049
75	12	0,85	100	212-0567
75	16	0,85	100	212-0570
75	19	0,85	100	212-7048
75	25	0,85	100	212-7050
100	12	0,85	100	212-0568
100	25	0,85	100	212-7051
150	25	0,85	100	212-0571



## Culture tubes, disposable, with screw cap

DURAN Group



### Soda-lime glass with DIN thread and PP screw cap

- Economical disposable culture tubes
- Food grade TPE gasket
- For use in applications without high thermal loads

Ø×L (mm)	Capacity (ml)	Wall thickness (mm)	Thread	Pk	Cat. No.
12×100	6	1	GL 14	100	391-0140
16×100	12	1	GL 18	100	391-0145
16×160	22	1	GL 18	100	391-0155
18×180	32	1	GL 18	100	212-0237