



Professional upright freezers, GGPv Liebherr



Temperature range from -10 to -35 °C

Commercial freezer models featuring automatic defrost.

- Indirect forced air cooling
- Electronic temperature controller with digital display, temperature and alarms
- Insulation 83 mm (temperature guaranteed at +43 °C)
- Automatic defrosting with evaporation of condensates
- Doors remain open at 90° and are self closing at less than 60°; reversible and lockable

Delivery information: These freezer cabinets are delivered with adjustable feet (150-180 mm), except models GGPV6570 and GGPV1470 which are supplied with castors.

Model	GGPv 6570	GGPv 1470
Capacity (l)	630	1430
Temperature (°C)	-10...-35	-10...-26
Display	Digital	
Defrost	Automatic	
Alarm	Audible and visual	
Shelves/drawers	4 plastic coated wire shelves/-	8 (2x4) plastic coated wire shelves/-
Door(s)	1 solid	2 solid
Door lock	Yes	
Material	Exterior and Interior: stainless steel	
Specifications	-	
WxDxH int. (mm)	510x650x1550	1240x650x1550
WxDxH ext. (mm)	700x830x2150	1430x830x2150
Weight (kg)	142	211

Type	Pk	Cat. No.
Upright freezer, GGPv 6570	1	472-1058
Upright freezer, GGPv 1470	1	472-1054



Laboratory freezers, MediLine, LGPv series Liebherr



Temperature range: -10 to -26 °C and -10 to -35 °C

These are heavy duty MediLine models with forced air cooling. The controller features door and temperature alarms which can be customised to suit the end user. Controller can be locked. The refrigerant used is hydrocarbon.

- Back-up battery for 7,5 days data logging and 72 hours battery back up for controller in case of mains failure
- RS485 interface connection, volt-free contacts, pre-drilled access port and optional infrared key for data download
- Forced air ventilation with hot gas defrost – for very small internal temperature variation
- Multi-function digital display and electronic temperature controller with temperature spikes due to electronically controlled defrost programs
- Ergonomic handle and self closing doors
- Equipped with castors, two with brakes, and plastic plastic coated wire shelves

Ordering information: A range of accessories like product temperature probe, data download key, RS485 interface converter, etc are available, please contact your local VWR sales office for further information. Temperature performance graphs available on request.

Model	LGPv 6520	LGPv 8420	LGPv 1420
Capacity (l)	600	856	1420
Temperature (°C)	-10...-35		-10...-26
Air circulation	Ventilated		
Display	LCD		
Defrost	Automatic		
Alarm	Audible and visual		
Shelves/drawers	4 adjustable grid shelves, plastic coated	5 shelves	8 adjustable grid shelves, plastic coated
Door(s)	1		2
Door lock	Yes		

Continued on next page