

RZR 2020 complete package

Sets are a convenient way to purchase the most popular products, at a more economical price. Package includes:

- Mechanical overhead stirrer RZR 2020
- Propeller type stirrer tool with pitched blade
- Universal stand
- Clamp

Description	Pk	Cat. No.
RZR 2020 complete package, UK-plug	1 Set	441-1311

Accessories for RZR overhead stirrers

Heidolph



441-1206



441-1208

Description	Pk	Cat. No.
Universal H-stand, base 425×420 mm, rod 25 mm Ø, height 700 mm	1	441-1206
Telescopic stand, H-shape, base 420×420, rod Ø 32 mm, height adjustable from 725 to 1025 mm	1	531-0375
Fastening clamp, diameter 13 - 32 mm (for RZR models)	1	441-1208
Chuck 8.5 mm. Chuck capacity 0.5 - 8.5 mm (for RZR 1)	1	441-1201
Chuck 10.5 mm. Chuck capacity 0.5 - 10.5 mm (for models RZR 2020, 2102)	1	441-1202
Shaft guard, plexiglass (PMMA), adjustable (for models RZR 2020, 2102)	1	441-1204
Stirrer guide (NS 29/32) with adjustable PTFE/Viton seal, accepts 8 mm Ø shaft	1	441-0279
Interface extension for RZR 2051 control and RZR 2102 control	1	441-1307

Mixing system, inoJET®

Heidolph



inoJET® 60 mm



inoJET® 80 mm



inoJET® 120 mm



inoJET® homogenises low and high-viscosity liquids in vessels by creating dynamic flow conditions by means of the so-called cone principle. Turbulent flows are created at the taper end by acceleration, displacement and retardation. These flows advance through the stirred medium and result in the new dynamic mixing motion.

- Only one system for nearly every mixing task
- No air intake, foaming or heating
- Careful and gentle mixing
- Short mixing periods
- Less power consumption through low mixing speed

Description	Material	Ø (mm)	For Ø (mm)	Shaft - Ø (mm)	Revolutions (min ⁻¹)	Pk	Cat. No.
inoJET® 60 mm	Stainless steel	60	80 - 150	10	200 - 800	1	441-0012
inoJET® 80 mm	Stainless steel	80	115 - 200	10	200 - 700	1	441-0013
inoJET® 80 mm	POM	80	115 - 200	10	200 - 700	1	441-0014
inoJET® 120 mm	Stainless steel	120	170 - 300	10	120 - 500	1	441-0015
inoJET® 120 mm	POM	120	170 - 300	10	120 - 500	1	441-0016