

Continued from previous page

Ø int. (mm)	Wall thickness (mm)	Colour code	Pk	Cat. No.
Two-stop configuration				
0,25	0,90	Orange/Blue	6	224-0550
0,38	0,90	Orange/Green	6	224-0551
0,51	0,90	Orange/Yellow	6	224-0552
0,64	0,90	Orange/White	6	224-0553
0,76	0,85	Black/Black	6	224-0554
0,89	0,85	Orange/Orange	6	224-0555
1,02	0,85	White/White	6	228-0584
1,14	0,85	Red/Red	6	224-0557
1,30	0,85	Grey/Grey	6	224-0558
1,42	0,85	Yellow/Yellow	6	224-0559
1,52	0,85	Yellow/Blue	6	224-0560
1,65	0,85	Blue/Blue	6	224-0561
1,85	0,85	Green/Green	6	224-0562
2,06	0,85	Violet/Violet	6	224-0563
2,29	0,85	Violet/Black	6	224-0564
2,54	0,85	Violet/Orange	6	224-0565
2,79	0,85	Violet/White	6	224-0566
Three-stop configuration				
0,25	0,90	Orange/Blue	6	228-0592
0,38	0,90	Orange/Green	6	228-0593
0,51	0,90	Orange/Yellow	6	224-0532
0,64	0,90	Orange/White	6	224-0533
0,76	0,85	Black/Black	6	224-0534
0,89	0,85	Orange/Orange	6	224-0535
1,02	0,85	White/White	6	224-0536
1,14	0,85	Red/Red	6	224-0537
1,30	0,85	Grey/Grey	6	224-0538
1,42	0,85	Yellow/Yellow	6	224-0539
1,52	0,85	Yellow/Blue	6	224-0540
1,65	0,85	Blue/Blue	6	224-0541
1,85	0,85	Green/Green	6	224-0542
2,06	0,85	Violet/Violet	6	224-0543
2,29	0,85	Violet/Black	6	224-0544
2,54	0,85	Violet/Orange	6	224-0545
2,79	0,85	Violet/White	6	224-0546



Tubing, Tygon[®], 3350 Saint-Gobain



Silicone, platinum cured, translucent

Tygon[®] tubing made from platinum cured silicone with ultra smooth surface. High elasticity with good restoring force for constant liquid transfer, even with intermittent pumping action.

- Biocompatible for sensitive applications, can be used for foodstuffs
- Resistant to ozone and UV, autoclavable
- FDA approved, compliant with USP class VI

Temperature resistance: -80 to +204 °C

Hardness (Shore durometer A): 50

Density: 1,14

Delivery information: Tubing is packed double bagged inside a cardboard box. Labelling the inner bag and the box with certificate of conformity and date of manufacture.

Ø int. (mm)	Ø ext. (mm)	Wall thickness (mm)	Pk	Cat. No.
1,60	3,20	0,80	15 m	228-4331
1,60	4,80	1,60	15 m	224-2101
2,40	4,00	0,80	15 m	228-0402
3,20	4,80	0,80	15 m	228-0403
3,20	6,40	1,60	15 m	228-4332
4,00	8,00	2,00	15 m	228-4334
4,80	8,00	1,60	15 m	224-2103
4,80	9,60	2,40	15 m	224-2106
6,40	9,60	1,60	15 m	228-4333
6,40	11,20	2,40	15 m	224-2107
6,40	12,80	3,20	15 m	224-2108
8,00	11,20	1,60	15 m	224-2105
8,00	12,00	2,00	15 m	228-4335
8,00	12,80	2,40	15 m	228-0636
9,50	12,70	1,60	15 m	228-0697

Continued on next page