

Continued from previous page

- Non scratch, prevents agitation vessels from being damaged
- Temperature resistant from -200 to +280 °C

Stirrer - Ø (mm)	Shaft - Ø (mm)	Shaft length (mm)	Pk	Cat. No.
Anchor stirrers				
80	6,0	400	1	441-9571
80	6,0	500	1	441-9572
140	9,5	550	1	441-9575
100	9,5	550	1	441-9573
140	9,5	650	1	441-9576
100	9,5	650	1	441-9574
Centrifugal stirrers				
40	6,0	400	1	441-9521
50	6,0	500	1	441-9522
70	9,5	550	1	441-9523
70	9,5	650	1	441-9524
Screw propellers				
40	6,0	400	1	441-9530
50	6,0	500	1	441-9532
60	9,5	550	1	441-9533
60	9,5	650	1	441-9534

KPG stirrers with lateral blade Lenz



DURAN®, borosilicate glass

With PTFE paddle and paddle safety securing screw. 10 mm shaft Ø. The length of the ground and polished bearing surface for the shaft Ø is 160 mm.

For container (ml)	Joint (NS)	Shaft - Ø (mm)	Shaft length (mm)	Blade LxW (mm)	Pk	Cat. No.
100	29/32	10	310	50x18	1	441-1000
250 - 500	29/32	10	310	68x24	1	441-9683
1000	29/32	10	390	75x24	1	441-1001
2000 - 3000	29/32	10	390	75x24	1	441-9682
2000 - 3000	45/40	16	460	75x24	1	441-1002
4000 - 5000	29/32	10	480	125x24	1	441-9679
4000 - 5000	45/40	16	520	125x35	1	441-1003
6000	45/40	16	560	125x35	1	441-1004
10000	45/40	16	620	125x35	1	441-1005



Stirring rods



Solid PTFE

- Inert and will not scratch, can be used up to 280 °C

Material	Length (mm)	Ø (mm)	Pk	Cat. No.
PTFE	150	8	5	442-4539
PTFE	250	8	5	442-4541
PTFE	300	8	5	442-4542