



Measuring cylinders Kartell



PP, highly translucent, tall form, autoclavable

- Pouring spout, pentagonal base assures excellent stability
- Non-wetting walls, absolutely no meniscus formation, very good chemical resistance
- Permanent, embossed graduations

ISO 6706, BS 5404

Capacity (ml)	Division (ml)	Tolerance (\pm ml)	Height (mm)	\varnothing (mm)	Pk	Cat. No.
10	0,2	0,2	140	13	1	612-0936
25	0,5	0,5	195	19	1	612-0937
50	1	1	199	26	1	612-0938
100	1	1	249	31	1	612-0939
250	2	2	315	41	1	612-0940
500	5	5	361	56	1	612-0941
1000	10	10	439	66	1	612-0942
2000	20	20	531	80	1	612-0943



Measuring cylinders Kartell



PP, translucent, tall form, autoclavable

- Pouring spout, pentagonal base and moulded blue graduations
- Autoclavable at +121 °C, can withstand temperatures up to +100 °C during continuous work

ISO 6706, BS 5404 Part 2

Capacity (ml)	Division (ml)	Tolerance (\pm ml)	Height (mm)	Pk	Cat. No.
10	0,2	0,2	140	1	612-4060
25	0,5	0,5	195	1	612-4061
50	1,0	1,0	199	1	612-4062
100	1,0	1,0	249	1	612-4063
250	2,0	2,0	315	1	612-4064
500	5,0	5,0	361	1	612-4065
1000	10,0	10,0	439	1	612-4066
2000	20,0	20,0	531	1	612-4067



THE VWR E-NEWSLETTER

Register now at
<http://eu.vwr.com/e-newsletter>