



Condensers, Allihn and Liebig type, with standard ground joints



PYREX®, borosilicate glass

With detachable polypropylene screw thread connectors with viton o-rings for use up to +140 °C. Allows 9 mm bore rubber and other flexible tubing to be attached to the condenser easily and safely.

- Very good chemical resistance
- High temperature resistance

Allihn Condenser

- Ideal for reflux applications
- Inner bulb sections provide increased cooling surface
- PP screw thread connectors

Liebig Condenser

- For distillation and reflux applications
- Water-jacketed
- PP screw thread connectors

Cone size (NS)	Socket size (NS)	Jacket length (mm)	Pk	Cat. No.
Condenser, Allihn				
19/26	-	250	1	201-8250
24/29	-	250	1	201-8307
29/32	-	250	1	201-8308
34/35	-	250	1	201-8309
40/38	-	250	1	201-8310
50/42	-	250	1	201-8311
24/29*	24/29	400	1	201-8312
Condenser, Liebig				
10/19**	10/19	60	1	201-8269
14/23	14/23	155	1	201-8270
19/26	19/26	208	1	201-8271
19/26	19/26	250	1	201-8255
24/29	24/29	250	1	201-8272
29/32	29/32	250	1	201-8257
24/29	24/29	395	1	201-8274
19/26	19/26	398	1	201-8273
29/32	29/32	400	1	201-8275
Description			Pk	Cat. No.
Accessories				
PP screw thread connector			10	201-8145
PTFE screw thread connector			10	216-1486
Spare viton o-ring			10	201-8146

* Only 201-8312 has a ground joint socket at the top of the condenser

**201-8269 does not have PP screw thread connectors but is fitted with glass olives because of size limitations



Condensers, double surface, Davies, with standard ground joints



PYREX®, borosilicate glass

Double surface, highly efficient condensers with a large cooling surface, inner cooling surface provides "baffle" effect whilst outer prevents "creep" with low boiling point liquids.

- Detachable plastic screw thread connector
- High chemical and temperature resistance

Cone size (NS)	Socket size (NS)	Jacket length (mm)	Pk	Cat. No.
14/23	14/23	160	1	201-8286
19/26	19/26	160	1	201-8287
24/29	24/29	160	1	201-8288
19/26	19/26	200	1	201-8289
24/29	24/29	200	1	201-8290
29/32	29/32	205	1	201-8291