

Continued from previous page

Capacity (ml)	Division (ml)	Tolerance (\pm ml)	Scale length (mm)	Pk	Cat. No.
Stopcock with glass key					
10	0,02	0,02	500	1	612-9967
25	0,05	0,03	500	1	612-9968
50	0,1	0,05	500	1	612-9969
Stopcock with PTFE spindle					
10	0,02	0,02	500	1	612-9970
25	0,05	0,03	500	1	612-9971
50	0,10	0,05	500	1	612-9972

Burettes, lateral stopcock, Schellbach, SILBERBRAND Brand



Borosilicate glass 3.3, class B

- Calibrated to deliver 'TD, Ex'
- Schellbach stripe, short marks at major graduations

DIN EN ISO 385

Length: 800 mm

Capacity (ml)	Division (ml)	Tolerance (\pm ml)	Pk	Cat. No.
Stopcock with PTFE spindle				
10	0,02	0,03	1	612-9964
25	0,05	0,05	1	612-9965
50	0,1	0,08	1	612-9966

Micro burettes, bang pattern, lateral stopcock, Schellbach, BLAUBRAND® Brand



Borosilicate glass 3.3, class AS, conformity certified

- Calibrated to deliver 'TD, Ex'
- Schellbach stripe, ring marks at major graduations
- With base

DIN EN ISO 385

Length: 900 mm except for 2 ml: 660 mm.

Ordering information: Supplied with a batch certificate. Burettes are also available on request with an individual certificate, a USP individual certificate or a DAkkS calibration certificate.

Capacity (ml)	Division (ml)	Tolerance (\pm ml)	Pk	Cat. No.
Stopcock with PTFE spindle				
2	0,01	0,01	1	612-9947
5	0,01	0,01	1	612-9948
10	0,02	0,02	1	661-1143
Stopcock with glass key				
2	0,01	0,01	1	612-9949
5	0,01	0,01	1	612-9950
10	0,02	0,02	1	612-9980

Automatic burettes, Dr. Schilling pattern, SILBERBRAND Brand



AR-GLAS®, class B

- Calibrated to deliver 'TD, Ex'
- Schellbach stripe, reduced distance between subdivision marks
- Automatic zeroing, squeezing bottle allows rapid filling, micrometre screw allows fine titration

Error limits according to class B, DIN EN ISO 385

With bottle: 500 ml for 10 and 15 ml; 1000 ml for 25 and 50 ml

Capacity (ml)	Division (ml)	Tolerance (\pm ml)	Total height (mm)	Pk	Cat. No.
Clear glass					
10	0,05	0,05	530	1	612-9920
15	0,1	0,08	510	1	612-9921
25	0,1	0,08	620	1	612-9922
50	0,1	0,10	830	1	612-9923