


Desiccators







Borosilicate glass 3.3

- With knobbed lids
- DIN 12491

| Nominal size (DN) | Usable height (mm) | Ø ext.×H (mm) | Ø int. (mm) | Pk | Cat. No. |
|-------------------|--------------------|---------------|-------------|----|----------|
| Desiccators | | | | | |
| 100 | 65 | 153×195 | 92 | 1 | 467-0069 |
| 150 | 95 | 215×265 | 143 | 1 | 467-0070 |
| 200 | 130 | 270×315 | 192 | 1 | 467-0071 |
| 250 | 140 | 320×370 | 239 | 1 | 467-0072 |
| 300 | 165 | 380×445 | 285 | 1 | 467-0073 |
| Tyne | | Ø (mm) | | Dl | Cat No |

| Туре | Ø (mm) | Pk | Cat. No. |
|-------------------|--------|----|----------|
| Desiccator plates | | | |
| Porcelain | 90 | 1 | 467-0100 |
| Porcelain | 140 | 1 | 467-0101 |
| Porcelain | 190 | 1 | 467-0102 |
| Porcelain | 235 | 1 | 467-0103 |
| Porcelain | 280 | 1 | 467-0104 |

Desiccator bases DURAN Group







With GL 32 MOBILEX

Without connection

With NS 24/29, NOVU

Ideal for drying and drying processes, storage under vacuum and protection from the effects of air and moisture. Applications include cultivation of organisms, material research and corrosion testing, cleaning equipment for analysis of trace elements, gas and liquid reactions and they can be used as a mini cleanroom for chip technology.

- Choice of various desiccator components to suit different applications
- Increased safety due to DURAN® quality borosilicate glass
- All models have flat flange
- Excellent mechanical, thermal and chemical resistance

Ordering information: Supplied without plate, lid or stopcock, please order required accessories separately.

| Туре | Nominal size (DN) | Usable height (mm) | Ø ext.×H (mm) | Pk | Cat. No. |
|----------------------|-------------------|--------------------|---------------|----|----------|
| Without connection | 100 | 58 | 153×112 | 1 | 467-1110 |
| Without connection | 150 | 81 | 215×154 | 1 | 467-1115 |
| Without connection | 200 | 118 | 270×202 | 1 | 467-1120 |
| Without connection | 250 | 122 | 320×235 | 1 | 467-1125 |
| Without connection | 300 | 154 | 380×283 | 1 | 467-1130 |
| With NS 24/29, NOVUS | 100 | 58 | 153×112 | 1 | 467-1210 |

Continued on next page

