



Quick action spigot, Nalgene®  
Thermo Scientific



PP, with HDPE tube adapter

Standard spigot for Nalgene® carboys.

- Very good chemical resistance, heat resistant up to +135 °C, autoclavable
- For tubes with 16 mm internal diameter
- With tube adapter for tubes with 6 to 9 mm internal diameter

Description	Pk	Cat. No.
Spigot for vessels	1	216-4423



Carboys, wide mouth, with screw cap, Nalgene®  
Thermo Scientific



PP, translucent with white PP screw cap, TPE seal

Ideal for large quantities of culture media, distilled water or other solutions.

- Very good chemical resistance
- Heat resistant up to +135 °C, autoclavable
- Extra wide opening, wide handles on the shoulders, leakproof closure

Capacity (l)	Height (mm)	Ø ext. (mm)	Neck I-Ø (mm)	Thread	Pk	Cat. No.
10	389	250	64	83B	1	216-8761
20	528	286	64	83B	1	216-8762
50	678	379	64	83B	1	216-8763



Carboys, wide mouth, with screw cap, Nalgene®  
Thermo Scientific



PPCO, translucent with white PP screw cap

Ideal for use in microbiology, perfect for handling large quantities of liquids, powders or other solids and pastes.

- Very good chemical resistance
- Heat resistant up to +121 °C, autoclavable
- Extra wide neck, wide handles on the shoulders, leakproof, graduated

Capacity (l)	Height (mm)	Ø ext. (mm)	Neck I-Ø (mm)	Pk	Cat. No.
10	343	250	88	1	216-4400
20	493	287	88	1	216-4401