

Burettes, straight stopcock, Schellbach, BLAUBRAND®
Brand



Borosilicate glass 3.3, class AS

- Calibrated to deliver 'TD, Ex', conformity certified
- Schellbach stripe, ring marks at major graduations
- Marks and inscriptions in high contrast blue enamel represent the optimum combination of resistance and readability

DIN EN ISO 385
Length: 800 mm

Ordering information: Supplied with a batch certificate. Burettes are also available on request with an individual certificate, a USP individual certificate or a DAkkS calibration certificate.

Capacity (ml)	Division (ml)	Tolerance (± ml)	Pk	Cat. No.
Stopcock with PTFE spindle				
10	0,02	0,02	1	612-9958
25	0,05	0,03	1	612-9959
50	0,10	0,05	1	612-9960
Stopcock with glass key				
10	0,02	0,02	1	612-9961
25	0,05	0,03	1	612-9962
50	0,10	0,05	1	612-9963

Burettes, straight stopcock, Schellbach
Hirschmann Laborgeräte



PTFE spindle



Glass key

DURAN®, borosilicate glass, class AS

- Calibrated to deliver 'Ex', conformity certified with dated batch identification
- Schellbach stripe, ring marks at major graduations, blue graduations

DIN EN ISO 385
Scale length: 500 mm

Table with 5 columns: Capacity (ml), Division (ml), Tolerance (± ml), Pk, Cat. No. It lists specifications for straight stopcocks with PTFE spindle and glass key in two sections.