



Hydrometers, M50 series



Glass hydrometers without thermometer, packed in a strong transparent plastic case.

- Conform to ISO 649 (BS 718, DIN 12791, NF B 35511)
- Calibration temperature: 20 °C
- Division 0,001 g/ml

Length: 270 mm

Range (g/ml)	Division (g/ml)	Pk	Cat. No.
0,800 - 0,850	0,001	1	614-0311
0,850 - 0,900	0,001	1	614-0312
0,900 - 0,950	0,001	1	614-0313
0,950 - 1,000	0,001	1	614-0314
1,000 - 1,050	0,001	1	614-0315
1,050 - 1,100	0,001	1	614-0316
1,100 - 1,150	0,001	1	614-0317
1,150 - 1,200	0,001	1	614-0318



Hydrometers, M100 series



Glass hydrometers without thermometer, packed in a strong transparent plastic case.

- Conform to ISO 649 (BS 718, DIN 12791, NF B 35511)
- Calibration temperature: 20 °C
- Division 0,002 g/ml

Length: 250 mm

Range (g/ml)	Division (g/ml)	Pk	Cat. No.
0,800 - 0,900	0,002	1	614-0109
0,900 - 1,000	0,002	1	614-0110
1,000 - 1,100	0,002	1	614-0111
1,100 - 1,200	0,002	1	614-0112
1,200 - 1,300	0,002	1	614-0113
1,300 - 1,400	0,002	1	614-0114

Hydrometers, general purpose



General purpose hydrometers for low and high surface tension.

- Calibration temperature: 20 °C
- Reading below the meniscus

Range (g/ml)	Division (g/ml)	Pk	Cat. No.
Division 0.001 g/ml, Length: 300 mm			
0,700 - 0,800	0,001	1	614-0023
0,800 - 0,900	0,001	1	614-0024
0,900 - 1,000	0,001	1	614-0025
1,000 - 1,100	0,001	1	614-0026
1,100 - 1,200	0,001	1	614-0027
1,200 - 1,300	0,001	1	614-0028
1,300 - 1,400	0,001	1	614-0029
1,400 - 1,500	0,001	1	614-0030
1,500 - 1,600	0,001	1	614-0031
1,600 - 1,700	0,001	1	614-0032
1,700 - 1,800	0,001	1	614-0033
1,800 - 1,900	0,001	1	614-0034
1,900 - 2,000	0,001	1	614-0035
Division 0.002 g/ml, Length: 300 mm			
0,600 - 0,800	0,002	1	614-0036
0,800 - 1,000	0,002	1	614-0037
1,000 - 1,200	0,002	1	614-0009
1,200 - 1,400	0,002	1	614-0038
1,400 - 1,600	0,002	1	614-0039
1,600 - 1,800	0,002	1	614-0040
1,800 - 2,000	0,002	1	614-0041