



Flasks, round bottom, with standard ground joints



PYREX®, borosilicate glass, clear

With white, matt labelling area.

- Very good chemical resistance
- High temperature resistance
- Minimal thermal expansion giving relatively high resistance to temperature changes

ISO 1773, ISO 4797

Socket size (NS)	Capacity (ml)	Height (mm)	Pk	Cat. No.
10/19	5	50	5	201-8528
14/23	5	65	5	201-8529
10/19	10	68	5	201-8466
14/23	10	68	5	201-8467
14/23	25	80	5	201-8497
19/26	25	80	5	201-8498
24/29	25	80	5	201-8499
14/23	50	90	5	201-8530
19/26	50	90	5	201-8531
24/29	50	95	5	201-8533
14/23	100	108	5	201-8468
19/26	100	108	5	201-8469
24/29	100	110	5	201-8471
29/32	100	114	5	201-8475
34/35	100	112	5	201-8476
19/26	150	114	5	201-8479
24/29	150	115	5	201-8481
29/32	150	120	5	201-8482
19/26	250	129	5	201-8500
24/29	250	130	5	201-8503
29/32	250	135	5	201-8509
34/35	250	138	5	201-8510
19/26	500	147	5	201-8534
24/29	500	150	5	201-8536
29/32	500	153	5	201-8542
34/35	500	166	5	201-8544
19/26	1000	177	2	201-8483
24/29	1000	180	2	201-8484
29/32	1000	183	2	201-8491
34/35	1000	196	2	201-8492
24/29	2000	215	1	201-8512
29/32	2000	220	1	201-8515
34/35	2000	228	1	201-8516
24/29	3000	236	1	201-8522
34/35	3000	249	1	201-8523
29/32	5000	270	1	201-8546
34/35	5000	280	1	201-8547
34/35	10000	350	1	201-8477



Flasks, round bottom, with standard ground joint VITLAB®



PFA, translucent

Can also be used as safety flasks for rotary evaporators.

- Very good chemical resistance
- Excellent thermal resistance from -270 to +250 °C
- Autoclavable

Socket size (NS)	Capacity (ml)	Height (mm)	Ø ext. (mm)	Pk	Cat. No.
29/32	100	117	65	1	214-1421
29/32	250	147	88	1	214-1422
29/32	500	177	107	1	214-1423