

Continued from previous page

Material	Exterior: steel, epoxy powder coated Interior: abrasion proof special plastic
WxDxH int. (mm)	440x435x1105
WxDxH ext. (mm)	600x615x2000
Weight (kg)	93

Type	Pk	Cat. No.
Combined fridge/freezer, white coated steel, LCv 4010, with right-hand reversible door hinges	1	471-0696



## Laboratory fridge/freezer with Comfort electronic controller and spark-free interior, MediLine Liebherr



Fridge/freezer with spark-free interior for storing explosive and highly flammable substances - for instance in the chemical industry or in special laboratories.

- Comfort electronic controller with digital temperature display enables temperatures to be set accurately
- Integrated data memory
- Dual controllers and dual compressors for optimum functionality
- 1-point calibration
- Access port for temperature sensor (Ø 10 mm)
- Convenient clear drawers (freezer part) with a transparent front providing a clear view of the products stored inside
- The doors are self-closing for convenient use, the door hinge is reversible and the gaskets are replaceable

Tested according to the 94/9 EC (ATEX 95) Directive. Rated as II 3G Ex nA II T6, suitable for storing explosive and highly flammable substances in sealed containers.

**Ordering information:** Please note that a non spark-free version is also available on request.

Model	LCexv 4010
Capacity (l)	Fridge: 240 Freezer: 105
Temperature (°C)	Fridge: +3...+8 Freezer: -9...-30
Display	Digital
Defrost	Fridge: automatic Freezer: manual
Alarm	Audible and visual
Shelves/drawers	Fridge: 4 glass shelves/- Freezer: 3 compartments
Material	Exterior: white coated steel Interior: fully moulded plastic, spark-free
WxDxH int. (mm)	Fridge: 440x435x1105 Freezer: 431x435x597
WxDxH ext. (mm)	Fridge: 600x615x2000
Weight (kg)	87

Type	Pk	Cat. No.
Laboratory fridge/freezer with Comfort electronic controller and spark-free interior, MediLine, LCexv 4010	1	471-1071

## Combined fridge/freezers, spark-free, Labcold



**Temperature range:** +2 to 8 °C (fridge); -17 to -23 °C (freezer)

For laboratory and general use where there is a concern that volatile or flammable materials or components might be stored. Spark-free interior in both compartments.

- Independent refrigeration control systems for both sections so that the refrigerator and freezer sections can be operated separately
- Model RLFF13246/LK has a lockable door
- CFC and HCFC free

**Ordering information:** For details of optional extras and accessories, e.g. battery powered temperature display and min/max recorder, please contact your local VWR sales office.

Model	RLFF13246/LK	RLFF13246
Capacity (l)	230/160	
Temperature (°C)	Fridge: 2...+8 Freezer: -17...-23	
Air circulation	Non ventilated	
Display	Optional	
Defrost	Automatic (refrigerator only)	

Continued on next page