



Graduated pipettes, type 3



AR-Glas®, class AS

- Calibrated to deliver (TD) type 3: Zero at the top
- Marks and inscriptions in amber stain
- With lot certificate

DIN 12696, ISO 835

Capacity (ml)	Division (ml)	Tolerance (\pm ml)	Pk	Cat. No.
0,5	0,01	0,0075	3	612-4767
1	0,01	0,01	3	612-4768
2	0,02	0,015	3	612-4769
5	0,1	0,045	3	612-4770
10	0,1	0,075	3	612-4771
20	0,1	0,15	2	612-4772
25	0,1	0,15	2	612-4773
50	0,2	0,3	2	612-4774



Graduated pipettes, type 3, total delivery



AR-Glas®, class B

- Calibrated to deliver (TD)
- Marks and inscriptions in amber stain
- With lot certificate

DIN 12696

Capacity (ml)	Division (ml)	Tolerance (\pm ml)	Pk	Cat. No.
0,5	0,01	0,008	3	612-4121
1	0,01	0,01	3	612-4122
2	0,02	0,015	3	612-4123
5	0,05	0,045	3	612-4124
10	0,1	0,075	3	612-4125
20	0,1	0,15	2	612-4126
25	0,1	0,15	2	612-4127
50	0,2	0,3	2	612-4128

Graduated pipettes, type 3, total delivery

Hirschmann Laborgeräte



AR-Glas®, class AS

- Calibrated to deliver 'Ex', certificate of conformity with dated batch identification available on internet (www.hirschmannlab.de)
- Marks and inscriptions in amber stain, graduated to the tip
- From 5 ml with a cotton plug as standard
- Waiting time 5 seconds

DIN EN ISO 835

Length: 360 mm \pm 5 mm except for 25 and 50 ml pipettes: 450 mm \pm 5 mm

Capacity (ml)	Division (ml)	Tolerance (\pm ml)	Pk	Cat. No.
0,5	0,01	0,006	1	612-1045
1	0,01	0,007	1	612-1046
1	0,1	0,007	1	613-2111
2	0,01	0,01	1	613-2112
2	0,02	0,01	1	612-1047
2	0,1	0,01	1	613-2113
5	0,05	0,03	1	612-1048
5	0,1	0,03	1	612-1049
10	0,1	0,05	1	612-1050
20	0,1	0,1	1	612-1051
25	0,1	0,1	1	612-1052
50	0,2	0,2	1	612-1053