

► Thermo Scientific Sterilin Cuvettes



Sterilin Cuvettes are suitable for use with most spectrophotometers for water analysis or chemistry and life science applications.

details

- Choice of material: optical quality polystyrene for use at visible wavelengths (340 to 900nm) or optical quality acrylic (PMMA) for use at ultraviolet wavelengths (300 to 900nm)
- Each case contains Cuvettes from the same mold cavity to ensure minimal dimensional variation
- Standard absorption variation between Cuvettes is better than ± 0.005 absorbency units
- Two sizes available — semi-micro Cuvette and macro Cuvette
- Standard pathlength of 10mm
- Frosted sides on the Cuvette provide an ideal labeling and handling area
- Recessed windows reduce the risk of scratching during use
- For ease of use an arrow feature indicates the direction of light transmission
- Packed in expanded polystyrene (EPS) foam trays for optimum protection ensuring scratch-free product at the time of use
- Supplied non-sterile

Ordering Information: Not available in all geographic regions

Notes: Cuvettes should not be used for long-term storage of samples. When using Hydrochloric acid, as the instrument can come under attack from the acid fumes, it is recommended that you use sealing film on the Cuvette.

Sterilin Cuvettes

Cat. No.	Description	Capacity	Material	Window W × H	Sterility	Inner Pack Qty.	Case Qty.
221M	Macro Cuvette	2.5 to 4.5mL	PS	10.0 × 32.5mm	NS	100	500
221S	Semi-micro Cuvette	1.5 to 3.0mL	PS	4.5 × 22.0mm	NS	100	500
222M	Macro Cuvette	2.5 to 4.5mL	PMMA	10.0 × 32.5mm	NS	100	500
222S	Semi-micro	1.5 to 3.0mL	PMMA	4.5 × 22.0mm	NS	100	500