

Tubing, PVC



PVC, transparent

Universal tubing for a wide range of applications. The preferred option where the flow of liquids has to be observed. Not suitable for operation under vacuum or pressure.

- High flexibility, good chemical resistance
- Smooth both inside and out, excellent resistance to abrasion
- Good value, large size rolls for customer-specific packaging

Temperature resistance: -20 to +60 °C

Hardness (Shore durometer A): 77

Ø int. (mm)	Ø ext. (mm)	Wall thickness (mm)	Pk	Cat. No.
1,00	1,80	0,40	100 m	228-3830
2,00	4,00	1,00	100 m	228-3831
3,00	4,00	0,50	100 m	228-3832
3,00	5,00	1,00	100 m	228-3833
3,00	6,00	1,50	100 m	228-3834
4,00	6,00	1,00	100 m	228-3835
4,00	7,00	1,50	100 m	228-3836
5,00	7,00	1,50	100 m	228-3837
6,00	8,00	1,00	100 m	228-3838
6,00	9,00	1,50	100 m	228-3839
6,00	10,00	2,00	50 m	228-3840
7,00	10,00	1,50	50 m	228-1252
7,00	11,00	2,00	50 m	228-3842
8,00	10,00	1,00	50 m	228-3843
8,00	11,00	1,50	50 m	228-3844
8,00	12,00	2,00	50 m	228-3845
9,00	12,00	1,50	50 m	228-3846
9,00	13,00	2,00	50 m	228-3847
10,00	14,00	2,00	50 m	228-3848
10,00	16,00	3,00	50 m	228-3849
12,00	16,00	2,00	50 m	228-3850
13,00	17,00	2,00	50 m	228-3851
15,00	19,00	2,00	50 m	228-3852
18,00	22,00	2,00	50 m	228-3853
20,00	26,00	3,00	50 m	228-3854
30,00	39,00	4,50	25 m	228-3855

Tubing, PVC, braided, Nalgene® Thermo Scientific



PVC, transparent

Braided, reinforced tubing is designed for high-pressure applications. It is more flexible than most competitive reinforced PVC tubing. This extra flexibility makes it easier to bend into place and permits tighter compression of crimp fittings for a secure fit. For easy identification and reordering, inside diameter and operating pressure are clearly imprinted in blue. Tubing contains DEHP, a commonly used plasticiser. Not suitable for medical applications.

- Tubing is made with food grade materials
- Excellent for use with weak acids, weak bases and salt solutions
- Not recommended for vacuum applications

Temperature resistance: -32 to +82 °C

Hardness (Shore durometer A): 65

Density: 1,34

Ø int. (mm)	Ø ext. (mm)	Wall thickness (mm)	Pk	Cat. No.
4,8	9,6	2,4	15 m	228-0193
6,4	11,2	2,4	15 m	228-0194
7,9	12,7	2,4	15 m	228-0195
9,5	14,3	2,4	15 m	228-0196
12,7	19,1	3,2	15 m	228-0197
15,9	22,3	3,2	15 m	228-0198
19,0	25,4	3,2	15 m	228-0199
25,4	33,4	4,0	15 m	228-0200