



Unstirred water baths with double walled, stainless steel (inner) and coated steel sheet (outer) housing. All baths except the 2 litre models feature a drain tap for convenient emptying and are suitable for use with water or alternatively with heat transfer beads. Baths with a capacity of 5 litres or more have a heat transfer bead mode which is activated through the main menu. A drain stopper (plug) is supplied as an optional accessory to ensure heat transfer beads do not get stuck in the drain outlet. Note: Baths are classified Safety Class 1, allowing unattended operation when used with non flammable liquids.

- Fast heat up, accurate temperature control
- Digital temperature indicator with three temperature presets
- Temperature range ambient +5 to 99 °C
- Temperature stability $\pm 0,2$ °C
- Adjustable over-temperature alarm protects samples from over heating
- Dry run protection turns the bath off if no water or low water level is detected
- Countdown timer and audible alarm: 1 to 999 minutes

Delivery information: Supplied with a hinged clear polycarbonate lid (the 2 litre models have an unhinged lid) and universal tray. A wide range of optional accessories are available.

Type	Temp. range (°C)	Temp. stability (°C)	Heating capacity (kW)	Capacity (l)	Bath WxDxH (mm)	WxDxH (mm)	Weight (kg)	Pk	Cat. No.
VWB2 2	Ambient +5...99	$\pm 0,2$	0,25	2	117x131x125	186x200x305	2,5	1	462-0554
VWB2 2S (shallow)	Ambient +5...99	$\pm 0,2$	0,35	2	289x139x40	335x215x260	3	1	462-0555
VWB2 5	Ambient +5...99	$\pm 0,2$	0,35	5	281x131x125	335x215x335	3,9	1	462-0556
VWB2 12	Ambient +5...99	$\pm 0,2$	0,8	12	306x281x125	335x390x380	6,2	1	462-0557
VWB2 18	Ambient +5...99	$\pm 0,2$	1,05	18	281x485x125	335x590x420	9,2	1	462-0558
VWB2 26	Ambient +5...99	$\pm 0,2$	1,05	26	278x481x175	335x590x430	9,4	1	462-0559

R & L Slaughter Ltd.
Unit 14, Carnival Park, Carnival Close,
Basildon, Essex. SS14 3WN
Tel: 01708 227140 Fax: 01708 228728
email: sales@slaughter.co.uk
website www.slaughter.co.uk