

Bulb pipettes

Hirschmann Laborgeräte



AR-Glas®, 1 mark, class B

- Calibrated to deliver (TD, Ex)
- Ring mark and inscriptions in amber stain

DIN 12690

Capacity (ml)	Tolerance (± ml)	Length (mm)	Suppl. to DIN	Pk	Cat. No.
0,5	0,0075	300	-	1	612-1348
1	0,0105	300	-	1	612-1349
2	0,015	330	-	1	612-1359
3	0,015	350	√	1	612-1350
4	0,023	400	√	1	612-3464
5	0,023	400	-	1	612-1351
10	0,03	440	-	1	612-1352
15	0,045	510	√	1	612-1353
20	0,045	510	-	1	612-1354
25	0,045	520	-	1	612-1355
50	0,075	540	-	1	612-1357
100	0,12	585	-	1	612-1358

Bulb pipettes

Brand



PP, highly translucent, 1 mark

- Calibrated to deliver (TD, Ex)
- Blue inscriptions
- Exposure to temperatures up to +60 °C will not cause permanent exceeding of tolerance limits
- Cleaning temperature below +60 °C is recommended to preserve marks and inscriptions
- Resistant to breakage

Capacity (ml)	Tolerance (± ml)	Length (mm)	Pk	Cat. No.
1	0,02	300 ± 10	1	612-1282
2	0,02	300 ± 10	1	612-1283
5	0,03	300 ± 10	1	612-1287
10	0,04	440 ± 10	1	612-1292
25	0,05	450 ± 10	1	612-1295
50	0,1	460 ± 10	1	612-1298

Weighing pipette, Lunge-Rey, Quickfit®



Pyrex® borosilicate glass

Precision-engineered, ground glass joints with a standard taper and smooth surface ensure complete interchangeability of elements with the same joint size and the highest standards of leak-tightness.

- Low coefficient of expansion, excellent chemical and heat resistance
- Specifically designed for weighing fuming or corrosive liquids
- All joints are 10/19
- Compatible with Erlenmeyer flask 201-8085

ISO 3585, DIN 12217

Description	Capacity (ml)	Pk	Cat. No.
Lunge-Rey weighing pipette	4	1	216-1487