

Continued from previous page

| Capacity (ml) | Thread (mm) | Ø ext. (mm) | Height (mm) | Neck I-Ø (mm) | Pk | Cat. No. |
|---------------|-------------|-------------|-------------|---------------|----|----------|
| 125 | 38 | 50 | 99 | 28 | 12 | 215-1043 |
| 250 | 43 | 61 | 131 | 33 | 12 | 215-1044 |
| 500 | 53 | 73 | 168 | 44 | 12 | 215-1045 |
| 1000 | 63 | 91 | 199 | 53 | 6 | 215-1046 |

Bottles, fluorinated, wide mouth, with screw cap, Nalgene®
Thermo Scientific



HDPE, with PP, fluorinate screw cap

Fluorinating these HDPE bottles provides a cost effective alternative to costly fluoropolymer containers.

- Safe, durable, fluorinated HDPE bottle has fluorocarbon surface, inside and out
- Fluorinated surface enhances long-term performance and prevents permeation loss
- Leakproof

| Capacity (ml) | Thread (mm) | Ø ext. (mm) | Height (mm) | Neck I-Ø (mm) | Pk | Cat. No. |
|---------------|-------------|-------------|-------------|---------------|----|----------|
| 2000 | 100 | 120 | 244 | 89 | 1 | 215-1032 |

Bottles, fluorinated, wide mouth, with screw cap, Nalgene®
Thermo Scientific



HDPE, fluorinated with PP screw cap

Fluorinating these HDPE bottles provides a cost effective alternative to costly fluoropolymer containers. Wide mouth makes filling and emptying of solid and liquid substances easier. Crack and impact resistant.

- Safe, durable, fluorinated HDPE bottle has fluorocarbon surface, inside and out
- Fluorinated surface enhances long-term performance and prevents permeation loss
- Leakproof

| Capacity (ml) | Thread (mm) | Ø ext. (mm) | Height (mm) | Neck I-Ø (mm) | Pk | Cat. No. |
|---------------|-------------|-------------|-------------|---------------|----|----------|
| 125 | 38 | 50 | 99 | 28 | 12 | 215-1039 |
| 250 | 43 | 61 | 131 | 33 | 12 | 215-1040 |
| 500 | 53 | 73 | 168 | 44 | 12 | 215-1041 |
| 1000 | 63 | 91 | 199 | 53 | 6 | 215-1042 |

Bottles, wide mouth, with screw cap, Nalgene®
Thermo Scientific



HDPE, translucent with PP screw cap

Economical, break resistant disposable bottles for safe sample collection, transport and storage. Suitable for long-term storage in the absence of direct UV radiation.

- Good chemical resistance
- Heat resistant from -100 °C to +120 °C
- Leakproof

| Capacity (ml) | Thread (mm) | Ø ext. (mm) | Height (mm) | Neck I-Ø (mm) | Pk | Cat. No. |
|---------------|-------------|-------------|-------------|---------------|----|----------|
| 30 | 28 | 34 | 63 | 21 | 72 | 215-1033 |
| 60 | 28 | 38 | 86 | 21 | 72 | 215-1034 |
| 125 | 38 | 51 | 100 | 28 | 72 | 215-1035 |
| 250 | 43 | 61 | 131 | 33 | 72 | 215-1036 |
| 500 | 53 | 73 | 168 | 44 | 48 | 215-1037 |
| 1000 | 63 | 91 | 199 | 52 | 24 | 215-1038 |