

di-Sodium sulphide in glycerine (25-50%)

Warning

H319 H315 H410
P280 P273 P302+P352 P305+P351+P338



CAS 1313-82-2

EINECS: 215-211-5

UN: 3266

ADR 8,III

Na₂S

M.W. 78.05 g/mol

Storage Temperature: Ambient temperature

di-Sodium sulphide 0.5 mol/l in glycerine 35% Reag. Ph. Eur. 1083901

Cat. No.	Pk	Pack type
87940.180	100 ml	Plastic bottle

Supplied with certificate of analysis. Normally manufactured to order. Please check with customer services.

Sodium sulphite

EUH031

CAS 7757-83-7

EINECS: 231-821-4

Na₂SO₃

M.W. 126.04 g/mol

Density: 2.63 g/cm³ (20 °C)

Melting Pt: Min. 500 °C

Storage Temperature: Ambient temperature

Sodium sulphite AnalR NORMAPUR® Reag. Ph. Eur. analytical reagent

Assay (at filling)..... Min. 98.0 % Colouration (10 %; water) Max. 10 APHA
Heavy metals (as Pb) Max. 20 ppm Fe (Iron) Max. 10 ppm

Cat. No.	Pk	Pack type
28130.260	500 g	Plastic bottle for solids
28130.292	1 kg	Plastic bottle for solids

Sodium sulphite, anhydrous Ph. Eur.

Assay 95.0 to 100.5 %
Appearance White powder
Identification A Passes test
Identification B Passes test
Identification C Passes test
Identification D Passes test
Solution S Passes test
Solution S1 Passes test
Appearance of solution Passes test
S₂O₃ (Thiosulphate) Max. 0.1 %
Fe (Iron) Max. 10 ppm
Se (Selenium) Max. 10 ppm
Zn (Zinc) Max. 25.0 ppm
Heavy metals (as Pb) Max. 10 ppm
Residual solvents Passes test

Cat. No.	Pk	Pack type
28125.294	1 kg	Plastic bottle for solids
28125.363	5 kg	Plastic bottle for solids
28125.465	25 kg	Bucket (Plastic)

Sodium sulphite, purified

Assay 95.0 to 100.5 %
Heavy metals (as Pb) Max. 50 ppm
Fe (Iron) Max. 20 ppm

Cat. No.	Pk	Pack type
28126.297	1 kg	Plastic bottle for solids
28126.366	5 kg	Bucket (Plastic)
28126.460	25 kg	Bucket (Plastic)

L(+)-Sodium tartrate dibasic dihydrate

See di-Sodium L(+)-tartrate dihydrate. p.458

di-Sodium L(+)-tartrate dihydrate

(R,R)-(+)-Disodium tartrate dihydrate, (R,R)-(+)-Tartaric acid disodium salt dihydrate, L(+)-Tartaric acid disodium salt dihydrate, (R,R)-(+)-Sodium tartrate dibasic dihydrate, L(+)-Sodium tartrate dibasic dihydrate, (+)-Disodium-L-tartrate dihydrate, (+)-Disodium L-tartrate dihydrate

CAS 6106-24-7

EINECS: 212-773-3

NaOOC(CHOH)₂COONa·2H₂O

M.W. 230.08 g/mol

Density: 1.818 g/cm³ (20 °C)

Melting Pt: 57 °C

di-Sodium L(+)-tartrate dihydrate GPR RECTAPUR®

Assay (calculated on anhydrous) Min. 99.0 %
Loss on drying (150°C) Max. 17.0 %
C₂O₄ (Oxalate) Max. 0.05 %
Cl (Chloride) Max. 50 ppm
As (Arsenic) Max. 2 ppm
Cu (Copper) Max. 10 ppm
Fe (Iron) Max. 10 ppm
Pb (Lead) Max. 10 ppm
Zn (Zinc) Max. 10 ppm

Cat. No.	Pk	Pack type
28174.260	500 g	Plastic bottle for solids

di-Sodium tetraborate

Danger

H360FD

P201 P281 P308+P313



CAS 1330-43-4

Index 005-011-00-4

EINECS: 215-540-4

Na₂B₄O₇

M.W. 201.22 g/mol

Density: 2.38 g/cm³ (20 °C)

Boiling Pt: 1575 °C (1013 hPa)

Melting Pt: 742 °C

Storage Temperature: Ambient temperature

VWR CHEMICALS di-Sodium tetraborate, ultrapure buffer substance

Appearance PASS
Conductivity (0.5%, Water) REPORT
DNase NONE
pH (0.5%, Water) 8.30 - 8.70
RNase NONE
Solubility PASS

Cat. No.	Pk	Pack type
1B1117-100G	100 g	Plastic bottle for solids
1B1117-500G	500 g	Plastic bottle for solids
1B1117-1KG	1 kg	Plastic bottle for solids

di-Sodium tetraborate, anhydrous TECHNICAL

Assay Min. 98 %

Cat. No.	Pk	Pack type
27716.290	1 kg	Plastic bottle for solids
27716.368	5 kg	Bucket (Plastic)