

Accessories for screw thread joints



For use with Quickfit® glass screw thread

Hole Ø (mm)	Thread	Pk	Cat. No.
Silicone rubber ring			
6,0 - 7,0	13	10	201-0572
7,0 - 8,5	18	10	201-0689
10,5 - 11,5	24	10	201-0690
6,0 - 7,0	24	10	201-0691
8,5 - 9,5	24	10	201-0692
10,5 - 11,5	28	10	201-0693
18,0 - 19,0	28	10	201-0694
6,0 - 7,0	28	10	201-0695



Adapter with ground joint and swivelling fittings with GL thread BOLA



Adapter with screw fitting made from PPS, cone joint body made from PTFE

For the insertion of probes, tubes and hoses into vessels with standard ground joints. To prevent contact with agitator shafts etc. Sensors, tubes or hoses are initially guided through the threaded connection. The adapter is then inserted in the joint and the inserted element (tube or probe) is secured in the required position.

- Very good chemical resistance
- Temperature resistant from -50 to +250 °C
- Suitable for vacuum applications

Cone size (NS)	Thread	Tube O-Ø (mm)	Pk	Cat. No.
19/26	GL 18	6	1	201-0275
29/32	GL 25	6	1	201-0268
29/32	GL 25	8	1	201-0269
29/32	GL 25	12	1	201-0270



Plastic screw caps with aperture DURAN Group



PBT, red without seals

With central hole.

- For DIN GL threads
- Heat resistant up to +180 °C
- Autoclavable

Hole Ø (mm)	Thread	Pk	Cat. No.
9,5	GL 14	1	201-1921
11,0	GL 18	1	201-1922
15,0	GL 25	1	201-1923
20,0	GL 32	1	201-1924
34,0	GL 45	1	201-1925