



Attachable screw thread tubes Lenz



DURAN®, borosilicate glass

DIN screw thread GL.

- Very good chemical resistance
- High temperature resistance
- Minimal thermal expansion giving relatively high resistance to temperature changes

Thread	Total length (mm)	Tube O-Ø (mm)	Pk	Cat. No.
GL 14	100	12	1	201-1601
GL 18	100	16	1	201-1602
GL 25	100	22	1	201-1606
GL 32	140	28	1	201-1607
GL 45	180	40	1	201-1608



Adapters with screw thread and standard ground joint cone Lenz



DURAN®, borosilicate glass

Threaded adapter with DIN thread and standard ground joint cone.

- Very good chemical resistance
- High temperature resistance
- Minimal thermal expansion giving relatively high resistance to temperature changes

DIN 12257

Cone size (NS)	Thread	Pk	Cat. No.
14/23	GL 14	1	201-1640
19/26	GL 14	1	275-1122
29/32	GL 14	1	201-1641
14/23	GL 18	1	201-1642
19/26	GL 18	1	201-1643
24/29	GL 18	1	201-1644
29/32	GL 18	1	201-1645
29/32	GL 25	1	201-1646
29/32	GL 32	1	201-1647

Adapters, cone/screw thread



Pyrex® borosilicate glass

Screw thread joint complete with plastic cap, silicone rubber ring and PTFE washer. Ideal for securing thermometers, gas inlet tubes etc.

- Very good chemical resistance
- High temperature resistance
- Minimal thermal expansion giving relatively high resistance to temperature changes

Cone size (NS)	Thread (mm)	Hole Ø (mm)	Pk	Cat. No.
14/23	13	6,0 - 7,0	2	201-0219
14/23	18	7,0 - 8,5	2	201-0696
19/26	13	6,0 - 7,0	2	201-0220
19/26	18	7,0 - 8,5	2	201-0225
19/26	24	10,5 - 11,5	2	201-0226
24/29	13	6,0 - 7,0	2	201-0697
24/29	18	7,0 - 8,5	2	201-0252
24/29	24	10,5 - 11,5	2	201-0227
29/32	13	6,0 - 7,0	2	201-0698
29/32	18	7,0 - 8,5	2	201-0228
29/32	24	10,5 - 11,5	2	201-0699
29/32	28	18,0 - 19,0	1	201-0702
34/35	28	18,0 - 19,0	1	201-0703