

NEW Conductivity standard 500 $\mu\text{S}/\text{cm}$ (25°C; 0.00345 mol/l; KCl) for conductivity measurement

Directly traceable to NIST, tested and certified to ISO17025
 Conductivity (25 °C) 495.0 to 505.0 $\mu\text{S}/\text{cm}$

Cat. No.	Pk	Pack type
84138.260	500 ml	Plastic bottle

Conductivity standard (1,000 - < 10,000 $\mu\text{S}/\text{cm}$; KCl)

CAS 7447-40-7
 EINECS: 231-211-8

KCl
 M.W. 74.55 g/mol
 Storage Temperature: Ambient temperature

NEW Conductivity standard 1,000 $\mu\text{S}/\text{cm}$ (25°C; 0.007 mol/l; KCl) for conductivity measurement

Directly traceable to NIST, tested and certified to ISO17025
 Conductivity (25 °C) 990.0 to 1010.0 $\mu\text{S}/\text{cm}$

Cat. No.	Pk	Pack type
84141.260	500 ml	Plastic bottle

Conductivity standard 1,413 $\mu\text{S}/\text{cm}$ (25°C; 0.01 mol/l; KCl) calibration solution for conductivity

Titer 0.00995 to 0.01005 mol/l
 Conductivity (25 °C) 1.39 to 1.43 mS/cm

Cat. No.	Pk	Pack type
83607.180	100 ml	Plastic bottle
83607.260	500 ml	Plastic bottle
83607.290	1 l	Plastic bottle

NEW Conductivity standard 1,413 $\mu\text{S}/\text{cm}$ (25°C; 0.01 mol/l; KCl) for conductivity measurement

Directly traceable to NIST, tested and certified to ISO17025
 Conductivity (25 °C) 1399 to 1427 $\mu\text{S}/\text{cm}$

Cat. No.	Pk	Pack type
84135.180	100 ml	Plastic bottle
84135.260	500 ml	Plastic bottle
84135.290	1 l	Plastic bottle

Conductivity standard 5,000 $\mu\text{S}/\text{cm}$ (25°C; 0.0375 mol/l; KCl) for conductivity measurement

Directly traceable to NIST, tested and certified to ISO17025

Cat. No.	Pk	Pack type
85645.260	500 ml	Plastic bottle

Conductivity standard (10,000 - < 100,000 $\mu\text{S}/\text{cm}$; KCl)

CAS 7447-40-7
 EINECS: 231-211-8

KCl
 M.W. 74.55 g/mol
 Density: 1.003 g/cm³ (20 °C)
 Storage Temperature: Ambient temperature

NEW Conductivity standard 10,000 $\mu\text{S}/\text{cm}$ (25°C; 0.0765 mol/l; KCl) for conductivity measurement

Directly traceable to NIST, tested and certified to ISO17025
 Conductivity (25 °C) 9900 to 10100 $\mu\text{S}/\text{cm}$

Cat. No.	Pk	Pack type
84146.260	500 ml	Plastic bottle

Conductivity standard 12,880 $\mu\text{S}/\text{cm}$ (25°C; 0.1 mol/l; KCl) calibration solution for conductivity

Directly traceable to NIST, tested and certified to ISO17025
 Conductivity (25 °C) 12.60 to 13.00 mS/cm

Cat. No.	Pk	Pack type
83608.260	500 ml	Plastic bottle
83608.290	1 l	Plastic bottle

NEW Conductivity standard 12,880 $\mu\text{S}/\text{cm}$ (25°C; 0.1 mol/l; KCl) for conductivity measurement

Directly traceable to NIST, tested and certified to ISO17025
 Conductivity (25 °C) 12751 to 13009 $\mu\text{S}/\text{cm}$

Cat. No.	Pk	Pack type
84136.180	100 ml	Plastic bottle
84136.260	500 ml	Plastic bottle
84136.290	1 l	Plastic bottle

NEW Conductivity standard 50,000 $\mu\text{S}/\text{cm}$ (25°C; KCl) for conductivity measurement

Directly traceable to NIST, tested and certified to ISO17025
 Conductivity (25 °C) 49500 to 50500 $\mu\text{S}/\text{cm}$

Cat. No.	Pk	Pack type
84142.260	500 ml	Plastic bottle

Conductivity standard (100,000 - < 1,000,000 $\mu\text{S}/\text{cm}$; KCl)

CAS 7447-40-7
 EINECS: 231-211-8

KCl
 M.W. 74.55 g/mol
 Storage Temperature: Ambient temperature

NEW Conductivity standard 100,000 $\mu\text{S}/\text{cm}$ (25°C; 0.85 mol/l; KCl) for conductivity measurement

Directly traceable to NIST, tested and certified to ISO17025
 Conductivity (25 °C) 99000 to 101000 $\mu\text{S}/\text{cm}$

Cat. No.	Pk	Pack type
84144.260	500 ml	Plastic bottle