

Continued from previous page

Ø int. (mm)	Ø ext. (mm)	Wall thickness (mm)	Pk	Cat. No.
1,60	4,80	1,60	7,5 m	228-1133
1,60	6,38	2,39	7,5 m	228-1134
2,01	3,02	0,51	7,5 m	228-1135
2,52	3,53	0,51	7,5 m	228-1136
3,00	4,01	0,51	7,5 m	228-1137
3,18	6,38	1,60	7,5 m	228-1138
3,18	7,95	2,39	7,5 m	228-1139
4,01	5,44	0,71	7,5 m	228-1140
4,78	7,98	1,60	7,5 m	228-0688
4,78	9,55	2,39	7,5 m	228-0666
4,78	9,86	2,54	7,5 m	228-1111
4,78	11,13	3,18	7,5 m	228-0667
6,35	9,55	1,60	7,5 m	228-1112
6,35	11,13	2,39	7,5 m	228-1113
6,35	11,43	2,54	7,5 m	228-1114
6,35	12,70	3,18	7,5 m	228-1115
6,35	13,21	3,43	7,5 m	228-1116
7,95	11,15	1,60	7,5 m	228-1118
7,95	12,73	2,39	7,5 m	228-0668
7,95	15,98	4,01	7,5 m	228-1119
9,53	14,30	2,39	7,5 m	228-1120
9,53	15,88	3,18	7,5 m	228-1121
9,53	16,38	3,43	7,5 m	228-0689
9,53	19,03	4,75	7,5 m	228-1122
12,01	20,03	4,01	7,5 m	228-1124
12,70	19,05	3,18	7,5 m	228-1125
12,70	19,56	3,43	7,5 m	228-0653
12,70	22,20	4,75	7,5 m	228-1126
15,88	22,23	3,18	7,5 m	228-1127
15,88	25,38	4,75	7,5 m	228-0669
16,00	24,03	4,01	7,5 m	228-1129
19,05	28,55	4,75	7,5 m	228-1130
25,40	34,90	4,75	7,5 m	228-1132
25,40	35,56	5,08	7,5 m	228-0690



## Tubing, silicone, HelixMark™, close tolerance

### Helix Medical



#### Silicone, translucent, platinum cured, for applications with very close tolerances

Tubing made from platinum cured Silastic® Q7-4750 material by Dow Corning, and satisfying requirements for biomedical/pharmaceutical use. The special manufacturing process ensures superior flow properties. The tubing is ideal for transfer operations, as well as other applications requiring non leachable material. Can be used at elevated temperatures, whilst resisting sticking or encrustation.

- Can be sterilised by autoclaving or ethylene oxide as well as by gamma radiation within the user's validated cycles and exposure levels
- Produced in accordance with GMP in an FDA-registered production facility for medical products
- Meets the biocompatibility requirements of USP Class VI and Eur. Ph. 3.1.9 and certified in accordance with ISO 10993-1 quality standards

Hardness (Shore durometer A): 50

**Delivery information:** Tubing is double bagged in crush resistant boxes. Material certification and lot traceability are included.

Ø int. (mm)	Ø ext. (mm)	Wall thickness (mm)	Pk	Cat. No.
3,18	6,35	1,59	15 m	228-1082
4,76	7,94	1,59	15 m	228-1083
6,35	9,53	1,59	15 m	228-1084
6,35	11,13	2,38	15 m	228-1085
9,53	14,29	2,38	15 m	228-1086
9,53	15,88	3,18	15 m	228-1087
12,70	17,46	2,38	15 m	228-1088
12,70	19,05	3,18	15 m	228-1089
15,88	22,23	3,18	15 m	228-1090