

## Bunsen burner

### Usbeck



Nickel plated brass with cast iron foot

- With air regulation and pilot flame
- Lever stop-cock

Height: 150 mm

Description	For	Head Ø (mm)	Type	Pk	Cat. No.
Lever stop-cock, Ø 14 mm	Natural gas	17	Bunsen	1	451-0081
Lever stop-cock, Ø 14 mm	Bottle gas	17	Bunsen	1	451-0082

## Cartridge burner

### Usbeck



Stainless steel

Propane/butane mix. For temperatures up to 1400 °C.

- With air regulation and needle valve

Ø×H: 105×215 mm

**Delivery information:** Supplied with cartridge, refill as accessory.

Description	For	Pk	Cat. No.
Burner with 400 ml cartridge	Butane/propane	1	451-2200
Cartridge burner with safety element	Butane/propane	1	451-0163

Description	Pk	Cat. No.
<b>Accessories</b>		
Gas cartridge, 400 ml	1	451-2201

## Cartridge burner



Brass with replaceable steel plated perforated head

Designed for use with butane/propane mix gas cartridges. This burner can achieve temperatures in excess of 1000 °C. The design of the gas cartridge enables the burner to be detached and re-attached as often as needed, making it easy to store and transport.

Typical burning time of the 220 g cartridge is 2¾ hours.

Description	For	Pk	Cat. No.
Burner with cartridge	Butane/propane	1	451-0046
Burner without cartridge	Butane/propane	1	451-0045

Description	Pk	Cat. No.
<b>Burner cartridge</b>		
Cartridge butane/propane, 220 g	1	451-0047