

Constructional Elements

Jointed/Distilling Elements


Still head, plain

Quickfit. Borosilicate glass. As preceding product but joints 19/26.

Pack 2

Q. Ref.	Cat. No.	£
SH4/2	201-8695	52.00D


Receivers



Receiver, Dean and Stark

Quickfit. Borosilicate glass, to BS 756, socket, cone and GP Rotaflo stopcock. Capacity 10ml divided 0.1ml, socket 19/26, cone 24/29, for light entrainers.

Q. Ref.	Cat. No.	/ 2+	£
WE6/23/10TL	201-8751	73.57	82.03D



Receivers, Dean and Stark

Quickfit. Borosilicate glass, to BS 756, with socket and cone for light entrainers. Socket size 19/26, cone size 24/29.

Cap. (ml)	Div. (ml)	Q. Ref.	Cat. No.	/ 2+	£
2	0.05	WE6/23/2	201-8752	36.87	41.11D
7.5	0.10	WE6/23/7	201-8754	41.96	46.79D
25	0.20	WE6/23/25	201-8753	51.73	57.68D



Arsenic determination apparatus

Quickfit. This apparatus is designed for the estimation of arsenic by the method which uses the formation of a complex between arsine and silver diethyl-dithiocarbamate with subsequent measurement at 538nm. This apparatus is also suitable for the estimation of antimony.

Q. Ref.	Pk	Cat. No.	£
1AD/1	1	201-8003	70.70D



Clips, PTFE for conical joints

For use with *Quickfit* glassware having conical joints, these clips are manufactured from PTFE to give maximum chemical resistance. Can be used at temperatures up to 250°C.

Joint size	Q. Ref.	Pk	Cat. No.	£
19/26	GC19	5	201-8557	13.57D
24/29	GC24	5	201-8558	13.84D
34/35	GC34	5	201-8559	14.11D
40/38	GC40	5	201-8560	14.91D




Clips, snap-fit

Manufactured from polyacetal. For use with *Quickfit* interchangeable jointed glassware. Can be used at temperatures up to 80°C. Considerably reduces the need for clamping.

Note These clips are **not** resistant to halogen gases or acids.


Joint size	Colour code	Q. Ref.	Pk	Cat. No.	£
14/23	Yellow	KC14	5	201-8566	9.89D
19/26	Blue	KC19	5	201-8567	10.34D
24/29	Green	KC24	5	201-8568	10.39D
29/32	Red	KC29	5	201-8569	10.81D
34/35	Orange	KC34	5	201-8570	11.43D



Clips, stainless steel

For use with flange joints.

Flange bore (mm)	Q. Ref.	Cat. No.	/ 5+	£
50	JC50F	201-8564	14.80	16.50D
75	JC75F	201-8565	15.68	17.49D
100	JC100F	201-8562	15.68	17.49D



Cold trap

Quickfit. Borosilicate glass, specifically designed for use in vacuum systems. The items may be used singly or connected in series. Socket size 24 / 29, refrigerant capacity 250ml.

Q. Ref.	Pk	Cat. No.	£
CT13/250	1	201-8299	97.59D