



Food processing gloves, VersaTouch™
Ansell



Nitrile, non sterile, powder-free, textured fingertips

These thin nitrile gloves are food contact approved and ideal for handling all fatty food. Typical applications include meal preparation, fruit, vegetable and dairy processing, food distribution and catering.

- Textured fingertips provide good comfort and tactility for sensitive, precise handling
- Beaded cuff prevents liquid from rolling onto the arm or wrist
- Latex-free: No risk of Type 1 allergies

Colour: White or blue

Length: 240 mm

Thickness: 0,075 mm

EN 374, Cat. III, AQL 1,5

Food contact approved

Type	Colour	Size	Pk	Cat. No.
100 gloves/dispenser				
92-200	Blue	6,5 - 7	100	112-1989
92-200	Blue	7,5 - 8	100	112-1992
92-200	Blue	8,5 - 9	100	112-1993
92-200	Blue	9,5 - 10	100	112-1994
92-205	White	6,5 - 7	100	112-2736
92-205	White	7,5 - 8	100	112-2737
92-205	White	8,5 - 9	100	112-2738
92-205	White	9,5 - 10	100	112-2739
100 gloves/polybag				
92-210	Blue	6,5 - 7	100	112-2740
92-210	Blue	7,5 - 8	100	112-2741
92-210	Blue	8,5 - 9	100	112-2742
92-210	Blue	9,5 - 10	100	112-2743
92-220	White	6,5 - 7	100	112-2744
92-220	White	7,5 - 8	100	112-2745
92-220	White	8,5 - 9	100	112-2746
92-220	White	9,5 - 10	100	112-2747



Gloves, Touch N Tuff® 92-600 and 92-605
Ansell



Nitrile, non sterile, powder-free, smooth finish or textured fingertips

These gloves with rolled cuffs are made of puncture resistant nitrile which offers valuable protection against accidental splashes of hazardous chemicals. Ideal for use in the chemical and electronics industry.

- 100% nitrile; no waxes, silicone or plasticisers; ideal for sensitive skin
- Three times the puncture resistance of latex or PVC
- Light, cool and durable
- Designed for maximum freedom of movement and minimum hand fatigue

Thickness: 0,12 mm

Colour: Green

EN 374, EN 1149-5 (tested for EN 1149-1 and 1149-3), Cat. III; AQL 1.5

Food contact approved

Type	Length (mm)	Size	Pk	Cat. No.
92-600	240	6,5 - 7	100	112-0997
92-600	240	7,5 - 8	100	112-0998
92-600	240	8,5 - 9	100	112-0999
92-600	240	9,5 - 10	100	112-1008
92-605	300	6,5 - 7	100	112-1935
92-605	300	7,5 - 8	100	112-1936
92-605	300	8,5 - 9	100	112-1937
92-605	300	9,5 - 10	100	112-1938