

Safety wash bottles, narrow mouth, printed, VITsafe™

VITLAB®



LDPE, translucent, with vent cap spray cap

Vent cap works on the principle of gas/vapour permeability. The screw cap prevents any build-up of vapour pressure above the contents. This prevents the risk of solvent dripping or leaking.

- Colour coded contents with hazard symbols and descriptions of hazards as required by the Hazardous Substance Ordinance
- Good chemical resistance
- Good thermal resistance
- GHS complaint symbols

Imprint	Capacity (ml)	Thread	Pk	Cat. No.
Acetone	250	GL 25	1	215-6841
Acetone	500	GL 25	1	215-6858
Acetone	1000	GL 32	1	215-6865
Acetic acid	500	GL 25	1	215-5706
Acetonitrile	500	GL 25	1	215-5705
Distilled water	500	GL 25	1	215-5716
Distilled water	1000	GL 32	1	215-6875
Ethanol	250	GL 25	1	215-6840
Ethanol	500	GL 25	1	215-5702
Ethanol	1000	GL 32	1	215-6878
Ethyl acetate	500	GL 25	1	215-5700
Isopropanol	250	GL 25	1	215-6874
Isopropanol	500	GL 25	1	215-5715
Isopropanol	1000	GL 32	1	215-6877
Methanol	250	GL 25	1	215-6873
Methanol	500	GL 25	1	215-5714
Methanol	1000	GL 32	1	215-6876
Methylene dichloride	500	GL 25	1	215-5708
Methylethylketone	500	GL 25	1	215-6864
N,N-Dimethylformamide	500	GL 25	1	215-5701

Wash bottles, slope shoulder, printed, Azlon®

SciLabware



LDPE translucent, colour coded PP closure with jet-tip aperture

- Indelibly printed with a choice of popular laboratory solvents, appropriate hazard symbols and CAS numbers
- Slim design offers comfortable handling and enhanced ease of use
- Jet tip aperture for fine control

Imprint	Capacity (ml)	Colour code	Pk	Cat. No.
Water	250	White	5	215-0580
Acetone	250	Red	5	215-3149
Isopropanol	250	Blue	5	215-3372
I.M.S.	250	Yellow	5	215-3374
Ethanol	250	Orange	5	215-0581
Water	500	White	5	215-0579
Acetone	500	Red	5	215-0582
Isopropanol	500	Blue	5	215-0401
I.M.S.	500	Yellow	5	215-3376
Ethanol	500	Orange	5	215-0583
Distilled water	500	White	5	215-3377

Wash bottles, wide mouth, Unitary™, Nalgene®

Thermo Scientific



LDPE, translucent, with PP screw cap

- Wide neck for quick, safe filling, leakproof closure
- Formed from a single piece, outlet tube can no longer become contaminated or leak. Jet tip can be cut to increase flow rate
- Good chemical resistance, heat resistant up to +80 °C

Capacity (ml)	Thread (mm)	Pk	Cat. No.
125	24	6	215-8111
250	38	4	215-8112
500	38	4	215-8113
750	38	4	215-8114
1000	43	2	215-8115