



High performance bottles, narrow mouth, with screw cap



LDPE, HDPE or PP with PP screw cap, translucent and amber

Ideal for storing and transporting liquids.

- LDPE heat resistant up to +80 °C
- HDPE heat resistant up to +120 °C
- PP heat resistant up to +135 °C, autoclavable
- Leakproof

Capacity (ml)	Thread	Ø ext. (mm)	Height (mm)	Pk	Cat. No.
LDPE, translucent					
8	20-410	25	44	12	215-3409
15	20-410	25	58	12	215-3410
30	20-410	33	69	12	215-3411
60	20-410	39	88	12	215-3412
125	24-410	51	98	12	215-3413
500	28-410	72	164	12	215-3414
1000	38-430	91	199	6	215-3415
2000	38-430	118	250	1	215-1917
HDPE, translucent					
4	13-415	16	41	12	215-3400
8	20-410	25	44	12	215-3401
15	20-410	25	58	12	215-3402
30	20-410	33	69	12	215-3403
60	20-410	39	88	12	215-3404
125	24-410	51	98	12	215-3405
250	24-410	61	133	12	215-3406
500	28-410	72	164	12	215-3407
1000	38-430	91	199	6	215-3408
HDPE, amber (to protect light-sensitive materials)					
4	13-415	16	41	12	215-3416
8	20-410	25	44	12	215-3417
15	20-410	25	58	12	215-3418
30	20-410	33	69	12	215-3419
60	20-410	39	88	12	215-3420
125	24-410	51	98	12	215-3421
250	24-410	61	133	12	215-3422
500	28-410	72	164	12	215-3423
1000	38-430	91	199	6	215-3424
PP, translucent, autoclavable					
8	20-410	25	44	12	215-3425
15	20-410	25	58	12	215-3426
30	20-410	33	69	12	215-2290
60	20-410	39	88	12	215-3427
125	24-410	51	98	12	215-3428
250	24-410	61	133	12	215-2291
500	28-410	72	164	12	215-3429
1000	38-430	91	199	6	215-3430



E-BUSINESS

More than just a webshop for all of your laboratory needs

Please visit us at vwr.com