



Culture vessels, cylindrical, with flat flange



PYREX®, borosilicate glass

Precision ground, flat flange joint. Ideal for fermentation and culture work.

- For use with Quickfit® flat flange lids and retaining clips
- Very good chemical resistance
- High temperature resistance

| Capacity (ml) | With | Height (mm) | Ø ext. (mm) | Pk | Cat. No. |
|---------------|---------------|-------------|-------------|----|----------|
| 1000 | flange 100 mm | 160 | 105 | 1 | 201-8553 |
| 2000 | flange 100 mm | 225 | 133 | 1 | 201-8555 |
| 5000 | flange 100 mm | 290 | 181 | 1 | 201-8556 |
| 10000 | flange 100 mm | 375 | 227 | 1 | 201-8552 |
| 20000 | flange 100 mm | 465 | 288 | 1 | 201-8554 |



Flat flange lids with 4 or 5 necks



PYREX®, borosilicate glass

With precision ground, flat flange joints.

- For use with Quickfit® reaction flasks and culture vessels
- Very good chemical resistance
- Minimal thermal expansion giving relatively high resistance to temperature changes

| Type | With | Neck | Side necks (NS) | Pk | Cat. No. |
|---------|---------------|-------------------|-------------------|----|----------|
| 4 Necks | flange 100 mm | NS 19/26 (centre) | 2×19/26 + 1×24/29 | 1 | 201-8579 |
| 5 Necks | flange 100 mm | NS 29/32 (centre) | 3×14/23 + 1×29/32 | 1 | 201-8062 |



Flat flange lids with 5 necks



PYREX®, borosilicate glass

With precision ground, flat flange joints.

- For use with Quickfit® reaction flasks and culture vessels
- Very good chemical resistance
- Minimal thermal expansion giving relatively high resistance to temperature changes

| | | | | | |
|----------------------|-------|--------|-------|-------|---|
| Centre Socket | | 19/26 | | 24/29 | |
| Flange bore (mm) | 75 | 100 | | | |
| Parallel socket (0°) | 14/23 | 19/26 | 14/23 | 19/26 | |
| Side (10°) socket | | 19/26 | | | |
| Side (15°) socket | 19/26 | - | 29/32 | 34/35 | |
| Side (5°) socket | | 19/26* | 14/23 | 19/26 | |
| Type | A | B | C | D | E |

Continued on next page