

► Thermo Scientific Sterilin Polystyrene Containers, 60 to 250mL



Sterilin Polystyrene Containers are ideal for sample containment.

details

- Choice of plastic or metal flow seal cap
- Leak-tested in accordance with BS EN 14254 Annexe D
- 125AM, 125BM and 125CM product certified 95kPa-compliant ensuring suitability for sample transport
- Aseptically manufactured
- *In vitro* use only

Ordering Information: Not available in all geographic regions

Certifications: CE marked in accordance with the European Directive 98/79/EC

CE

95kPa

Aseptic

Sterilin Polystyrene Containers, 60 to 250mL

Cat. No.	Description	Label	Material Base/Cap	O.D. x H	Sterility	Case Qty.
60mL						
125AM†	Metal cap	None	PS/ME	44.5 × 61.0mm	AS	300
125BM†	Metal cap	Printed	PS/ME	44.5 × 61.0mm	AS	300
125CM†	Metal cap	Plain	PS/ME	44.5 × 61.0mm	AS	300
125AP	Plastic cap	None	PS/PE	35.0 × 61.0mm	AS	300
125BP	Plastic cap	Printed	PS/PE	35.0 × 61.0mm	AS	300
125CP	Plastic cap	Plain	PS/PE	35.0 × 61.0mm	AS	300
100mL						
185AM	Metal cap	None	PS/ME	49.5 × 77.0mm	AS	200
185BM	Metal cap	Printed	PS/ME	49.5 × 77.0mm	AS	200
185CM	Metal cap	Plain	PS/ME	49.5 × 77.0mm	AS	200
185AP	Plastic cap	None	PS/PE	51.0 × 78.0mm	AS	200
185BP	Plastic cap	Printed	PS/PE	51.0 × 78.0mm	AS	200
185CP	Plastic cap	Plain	PS/PE	51.0 × 78.0mm	AS	200
150mL						
165A	Metal cap	None	PS/ME	55.0 × 108.0mm	AS	120
165B	Metal cap	Printed	PS/ME	55.0 × 108.0mm	AS	120
165C	Metal cap	Plain	PS/ME	55.0 × 108.0mm	AS	120
250mL						
190A	Metal cap	None	PS/ME	65.5 × 119.5mm	AS	50
190B	Metal cap	Printed	PS/ME	65.5 × 119.5mm	AS	50
190C	Metal cap	Plain	PS/ME	65.5 × 119.5mm	AS	50

† 95kPa compliant