



Microcentrifuge, Micro Star 12



Safe and easy to use centrifuge delivering optimum performance in a compact unit. All operating parameters, including rpm, RCF and remaining time, are set and displayed digitally. It has an automatic lid release, pulse spin function for fast, convenient quick spins and an unique internal airflow design to reduce the heating up of samples.

- Compact design with small footprint
- Rapid acceleration and deceleration together with quiet operation characteristics
- Automatic detection for imbalance
- Alarms for over speed and over heat
- Autoclavable rotor for 12x1,5/2,0 ml tubes includes biosafety rotor lid

Ordering information: Supplied with fixed angle microtube rotor and adapters for 0,2 ml PCR tubes (pack of 12).

Model	Micro Star 12
Max. capacity	12x1,5/2,0 ml
Max. speed (min ⁻¹)	13500
Max. RCF (xg)	12300
Timer	1–30 min
Power supply	230 V / 50-60 Hz
WxDxH (mm)	208x245x145
Weight (kg)	4,4

Description	Pk	Cat. No.
Microcentrifuge Micro Star 12	1	521-1651

Description	Pk	Cat. No.
Accessories		
Rotor for 4x(8x0,2 ml) PCR strips	1	521-1652
Adapters for 0,2 ml PCR tubes (pack of 12)	12	521-1653
Adapters for 0,5 ml microtubes (pack of 12)	12	521-1654



Microcentrifuge, MiniStar silverline



This centrifuge was developed for applications that do not require high speed centrifugation, such as microfiltration and cell separation, and can also be used in a cold room. Metal base with ABS body and transparent safety cover. On closing the lid, the rotor quickly accelerates to maximum speed. Pressing the button on the front of the unit stops operation and opens the lid. Alternatively, the unit can be turned on and off with the switch at the back.

- Quiet and compact design
- Starts and stops in seconds
- Easy to operate, for eight microtubes or four strip tubes

Ordering information: MiniStar silverline supplied with 8x1,5/2,0 ml rotor, 4x(8x0,2 ml) strip tube rotor, eight adapters for 0,5 ml and eight adapters for 0,4 ml tubes.

Model	MiniStar silverline
Max. capacity	8x1,5/2,0 ml tubes or 4x(8x0,2 ml) tube strips
Max. speed (min ⁻¹)	6000
Max. RCF (xg)	2000
Noise level (dB(A))	57
WxDxH (mm)	132x155x110
Weight (kg)	0,75

Description	Pk	Cat. No.
MiniStar silverline with rotors and adapters, UK-plug	1	521-2845

Description	Pk	Cat. No.
Accessories		
Rotor for 8x1,5/2,0 ml tubes	1	521-2847
Rotor for 4 strips of 8x0,2 ml tubes	1	521-2848