

Tubing, silicone, Syndev®



Silicone, translucent, food grade

Suitable for peristaltic pumps, endoscopy, laparoscopy, most food processing applications and many other non critical medical, laboratory, pharmaceutical and biotechnical applications.

- Peroxide cured
- Manufactured to GMP in a clean room, FDA compliant to food grade regulation 177.2600 and certified to the biocompatibility requirements of USP Class VI.

Temperature resistance: -60 to +220 °C

Hardness (Shore durometer A): 60 ±5

Ø int. (mm)	Ø ext. (mm)	Wall thickness (mm)	Pk	Cat. No.
0,30	0,63	0,165	15 m	228-0228
0,50	0,93	0,215	15 m	228-0229
0,63	1,19	0,280	15 m	228-0230
0,76	1,65	0,445	15 m	228-0231
1,57	4,77	1,600	15 m	228-0234
1,98	3,17	0,595	15 m	228-0235
2,64	4,87	1,115	15 m	228-0236
3,35	4,64	0,645	15 m	228-0237
3,17	6,35	1,590	15 m	228-0238
4,74	7,92	1,590	15 m	228-0239
4,74	9,52	2,390	15 m	228-0240
6,35	9,52	1,585	15 m	228-0241
6,35	11,09	2,370	15 m	228-0242
6,35	12,70	3,170	15 m	228-0243
7,92	11,09	1,585	15 m	228-0244
7,92	12,70	2,390	15 m	228-0245
9,52	12,70	1,590	15 m	228-0246
9,52	14,27	2,380	15 m	228-0247
12,7	15,87	1,585	7,6 m	228-0248
12,7	17,44	2,370	7,6 m	228-0249
12,7	19,05	3,175	7,6 m	228-0250
15,87	22,22	3,175	7,6 m	228-0251
19,05	25,40	3,175	7,6 m	228-0252



Tubing, silicone, HelixMark™ Helix Medical



Silicone, translucent, platinum cured

Biomedical/pharmaceutical grade tubing, manufactured by Wacker Silicones from HM-6540 platinum cured material. The special manufacturing process minimises flow degradation over extended periods.

- Can be sterilised by autoclaving or ethylene oxide as well as by gamma radiation within the user's validation cycles and exposure levels
- Manufactured according to GMP in an FDA-registered production facility for medical products
- Compliant with the biocompatibility requirements of USP, Class VI

Hardness (Shore durometer A): 54

Density: 1.15

Delivery information: Tubing is double shrink wrapped in crush resistant boxes. Material certification and lot traceability are included.

Ø int. (mm)	Ø ext. (mm)	Wall thickness (mm)	Pk	Cat. No.
0,31	0,64	0,15	15 m	228-0661
0,76	1,65	0,46	15 m	228-1091
2,64	4,88	1,12	15 m	228-1092
3,35	4,65	0,66	15 m	228-1093
3,18	6,35	1,59	15 m	228-1094
4,76	7,94	1,59	15 m	228-1095
4,76	9,53	2,38	15 m	228-1096
6,35	9,53	1,59	15 m	228-1097
6,35	11,11	2,38	15 m	228-1098
6,35	12,70	3,18	15 m	228-1099
7,94	12,70	2,38	15 m	228-0662
9,53	12,70	1,59	15 m	228-0663
9,53	14,29	2,38	15 m	228-1100
9,53	15,88	3,18	15 m	228-1101
12,70	19,05	3,18	15 m	228-0664
15,88	22,23	3,18	15 m	228-1104
19,05	25,40	3,18	15 m	228-0845