

Continued from previous page

Description	For bottles	Thread (mm)	For	Pk	Cat. No.
Screw caps					
Screw cap	50/100/200	18	Narrow mouth bottles	1	215-3510
Screw cap	250/500	25	Narrow mouth bottles	1	215-3511
Dropper caps					
Dropper cap with nozzle	50/100/200	18	Narrow mouth bottles	1	215-1409
Dropper cap with nozzle	250/500 ml (1000 ml)	25	Narrow mouth bottles	1	215-0920
Spray caps for narrow mouth bottles					
Wash bottle closure	250	25	Narrow mouth bottles	1	215-1406
Wash bottle closure	500	25	Narrow mouth bottles	1	215-6322
Wash bottle closure	1000	28	Narrow mouth bottles	1	215-1407

Bottles, narrow mouth, square with thread
KAUTEX TEXTRON



HDPE, translucent or HDPE, white, without cap

Ideal for collecting, storing and shipping samples or storing liquids. Square shape saves space. Recessed labelling space. Leakproof.

- Good chemical resistance
- Resistant to temperatures from -40 to +110 °C
- Caps in four designs optionally available

Capacity (ml)	Thread (mm)	WxDxH (mm)	Pk	Cat. No.
Bottles, HDPE, translucent				
100	32	45x45x108	1	215-2366
250	32	60x60x136	1	215-2367
500	32	74x74x170	1	215-2368
1000	32	85x85x221	1	215-2369
2500	45	122x122x272	1	215-1405

Description	For bottles (ml)	Thread (mm)	Pk	Cat. No.
Screw closures for narrow mouth square bottles with thread				
Screw closure, PP, red, with pull-off ring and PE-foam insert	100 - 1000	32	1	215-2352
Screw Closure, PP, blue, with pull-off ring and conical seal	100 - 1000	32	1	215-3357
Screw Closure, PP, blue, with pull-off ring and conical seal	2500	45	1	215-3361
Screw closure, PP, white/blue, child resistant, with tamper evident ring and conical seal	100 - 1000	32	1	215-2355
Screw closure, PP, white/red, child resistant, with tamper evident ring, conical seal and degassing membrane	100 - 1000	32	1	215-2356

Bottles, narrow mouth, square, with screw cap, Nalgene®
Thermo Scientific



HDPE, translucent or PPCO, translucent, with PP screw cap

Ideal for storing and shipping liquids. Graduated.

- **HDPE:** Good chemical resistance. **PPCO:** Very good chemical resistance
- **HDPE:** Heat resistant up to +120 °C. **PPCO:** Heat resistant up to +135 °C, autoclavable
- Leakproof

Capacity (ml)	Thread (mm)	WxDxH (mm)	Material	Neck I-Ø (mm)	Pk	Cat. No.
30	20	38x38x64	HDPE/PP	14	12	215-7641
30	20	38x38x64	PPCO	14	12	215-7621
60	24	41x41x83	HDPE/PP	18	12	215-7642
60	24	41x41x83	PPCO	18	12	215-7622
125	38-430	54x54x110	HDPE/PP	28	12	215-7643
125	38-430	54x54x110	PPCO	28	12	215-7623
250	38-430	61x61x146	HDPE/PP	28	12	215-7644
250	38-430	61x61x146	PPCO	28	12	215-7624
500	38-430	74x74x177	HDPE/PP	28	12	215-7645
500	38-430	74x74x177	PPCO	25	12	215-7625
1000	38-430	94x94x220	HDPE/PP	28	6	215-7646
1000	38-430	94x94x220	PPCO	28	6	215-7626