



Digital burettes, Titrette® Brand



Variable volume

Titrate quickly and reliably with high precision, even in close quarters, with no power connection needed.

The Titrette® has an innovative measuring system – the tight error limits* of class A glass burettes as per DIN EN ISO 385 are met.

- Light and flexible burette with compact design and high accuracy
- Smooth-running operation with large, easy-grip hand wheels for sensitive, dropwise titration
- Easier use: Adjustment with easy calibration, calibration schedule to save a date for the next calibration, save power with Automatic Off function, change decimal place settings
- Easy to dismantle: Cleaning, maintenance and part replacement
- PC interface - optional - for data transmission directly to the PC, which eliminates transcription errors during transcription of the primary data to fulfill an important GLP requirement

Delivery information: Titrette® bottle-top burette, conformity certified, supplied with performance certificate, telescopic filling tube (170 - 330 mm), recirculation tube, two micro batteries (AAA/UM4/LR03), three bottle adapters PP (GL 45/32, GL 45/S 40 and GL 32/NS 29/32), two coloured light shield inspection windows, operating manual. Additional items supplied when ordering the Titrette® with PC interface: Connector cable - Sub-D plug connector, 9-pin - and a CD with driver software, communication protocol, example application and a special operating manual.

Volume (ml)	Division (ml)	Accuracy (%)	Imprecision (%)	Pk	Cat. No.
Standard					
10	0,001	±0,10	<0,05	1	613-2314
25	0,001	±0,07	<0,025	1	613-0795
50	0,002	±0,06	<0,02	1	613-0796
With RS232 interface					
25	0,001	±0,07	<0,025	1	613-0905
50	0,002	±0,06	<0,02	1	613-0906
Description				Pk	Cat. No.
Accessories for Titrette®					
Two sets of inspection windows, clear and amber coloured for protection of light-sensitive media				1	613-3742
Telescopic filling tubes, FEP, 25/50/100 ml, o. Ø 7,6 mm, 170 - 330 mm				1	613-0467
Telescopic filling tubes, FEP, 25/50/100 ml, o. Ø 7,6 mm, 250 - 480 mm				1	612-5603
Piston head, 25 ml				1	613-3744
Piston head, 50 ml				1	613-3745
Titrating tube with screw cap and integrated discharge and recirculation valve				1	613-3743
Dispensing cylinder with valve head, 25 ml, until serial no. 12 J				1	613-3746
Dispensing cylinder with valve head, 50 ml, until serial no. 12 J				1	613-3747

* Error limits relate to the nominal volume.



ALL YOU NEED FOR CHEMICAL ANALYSIS

A great companion for chemists in any industry

- Sampling and sample preparation
- Spectroscopy, chromatography and physical measurement
- Waste and hazard management

Request your copy from your local VWR sales office or vwr.com