

Continued from previous page

Gauge	Volume (µl)	Length (mm)	Ø ext. (mm)	Type	Type of tip	Pk	Cat. No.
26s	5	51	0,48	75 N	2	1	549-1230
26s	5	51	0,48	75 RN	2	1	549-1231
-	10	-	-	701 LT	-	1	549-0221
23s-26s	10	43	0,72 - 0,47	701 N	AS	6	549-1276
26s	10	51	0,47	701 RN	2	1	549-1137
26s	10	51	0,47	701 N	2	6	549-1140
26s	10	51	0,47	701 N	3	1	549-0223
26s	10	51	0,47	701 N	2	1	549-1135
26s	10	70	0,47	701 N	2	1	549-1138
-	25	-	-	702 LT	-	1	549-0363
22s	25	51	0,72	702 RN	2	1	549-1149
22s	25	51	0,72	702 N	2	1	549-1144
-	50	-	-	705 LT	-	1	549-0225
22s	50	51	0,72	705 N	2	1	549-1153
22s	50	51	0,72	705 RN	2	1	549-1154
-	100	-	-	710 RN	-	1	548-1535
-	100	-	-	710 LT	-	1	549-0227
22s	100	51	0,72	710 N	2	1	549-1156
22s	100	51	0,72	710 RN	2	1	549-1157
-	250	-	-	725 LT	-	1	549-0228
22s	250	51	0,72	725 N	2	1	549-1159
22s	250	51	0,72	725 RN	2	1	549-1162
-	500	-	-	750 LT	-	1	549-0229
-	500	-	-	750 RN	-	1	548-1536
22	500	51	0,72	750 N	2	1	549-1166
22	500	51	0,72	750 RN	2	1	549-1167

## 800 series Microliter™ syringes Hamilton



Universal injection syringes for GC. Similar to the 700 series but with a reinforced, protected plunger.

- Extended handle simplifies sampling from test tubes or long-necked flasks
- Available with a standard 51 mm needle: cemented (N) or removable (RN)

Gauge	Volume (µl)	Length (mm)	Ø ext. (mm)	Type	Type of tip	Pk	Cat. No.
26s	5	51	0,47	85 N	2	1	549-1202
26s	5	51	0,47	85 RN	2	1	549-1203
26s	10	51	0,47	801 N	2	1	549-1204
26s	10	51	0,47	801 RN	2	1	549-1205
22s	25	51	0,72	802 N	2	1	549-1206
22s	25	51	0,72	802 RN	2	1	549-1207
22s	50	51	0,72	805 N	2	1	549-1208
22s	50	51	0,72	805 RN	2	1	549-1209
22s	100	51	0,72	810 N	2	1	549-1210
22s	100	51	0,72	810 RN	2	1	549-1211
22s	250	51	0,72	825 RN	2	1	549-1213

Description	Volume (µl)	Type	Pk	Cat. No.
<b>Accessories</b>				
Barrel/plunger assembly	10	801 RN	1	549-0215

## 1000 series Gastight® syringes Hamilton



Gas-tight syringes for use with gases or liquids.

- PTFE plunger tip creates a leak-free seal
- Syringe glass barrel and plunger are interchangeable