

Sodium hydroxide, pellets GPR RECTAPUR®

Assay	Min. 98 %
Heavy metals (as Pb)	Max. 5 ppm
Total N (Nitrogen)	Max. 5 ppm
CO ₃ (as Na ₂ CO ₃)	Max. 1.0 %
Cl (Chloride)	Max. 50 ppm
PO ₄ (Phosphate)	Max. 20 ppm
SiO _x (as SiO ₂)	Max. 100 ppm
SO _x (Sulphate)	Max. 50 ppm
Al (Aluminium)	Max. 10 ppm
Fe (Iron)	Max. 10 ppm
K (Potassium)	Max. 0.1 %
Pb (Lead)	Max. 5 ppm

Cat. No.	Pk	Pack type
28245.265	500 g	Plastic bottle for solids
28245.298	1 kg	Plastic bottle for solids
28245.320	2,5 kg	Plastic bottle for solids
28245.367	5 kg	Plastic bottle for solids
28245.460	25 kg	Bucket (Plastic)

VWR CHEMICALS Sodium hydroxide, pellets, proteomics grade

Chloride	0.005 %
DNase	NONE
Heavy Metals	0.002 %
Iron	0.001 %
Mercury	0.1 ppm
Nickel	0.001 %
Nitrogen Compounds	0.001 %
Phosphate	0.001 %
Potassium	0.02 %
Protease	NONE
Purity	97.0 %
RNase	NONE
Sodium Carbonate	1.0 %
Sulfate	0.003 %

Cat. No.	Pk	Pack type
M137-500G	500 g	Plastic bottle for solids
M137-1KG	1 kg	Plastic bottle for solids

Sodium hydroxide, pellets Selectipur® for the electronics industry

Cat. No.	Pk	Pack type
52111071.	300 kg	Plastic drum

This product is not available in all countries. Please check with your local VWR International office or supplier.

Sodium hydroxide, shots TECHNICAL

Assay	Min. 97.0 %
Sodium carbonate	Max. 1.5 %

Cat. No.	Pk	Pack type
28240.292	1 kg	Plastic bottle for solids
28240.361	5 kg	Bucket (Plastic)
28240.460	25 kg	Bucket (Plastic)

Sodium hydroxide (5 - < 60%) in aqueous solution

Danger

H314
P280 P301+P330+P331 P305+P351+P338
P309+P310

CAS 1310-73-2

EINECS: 215-185-5

UN: 1824

ADR 8,II

NaOH

Density: 1.53 g/cm³ (20 °C)

Boiling Pt: 119 to 135 °C (1013 hPa)

Melting Pt: 9 to 10 °C

Storage Temperature: Ambient temperature

Sodium hydroxide 50% in aqueous solution
Reag. Ph. Eur. 1081406 carbonate free

Cat. No.	Pk	Pack type
87938.290	1 l	Plastic bottle

Supplied with certificate of analysis. Normally manufactured to order. Please check with customer services.

Sodium hydroxide 50% in aqueous solution
GPR RECTAPUR®

Assay	47 to 51 %
Sodium carbonate	Max. 0.5 %
Heavy metals (as Pb)	Max. 20 ppm
Cl (Chloride)	Max. 50 ppm
Fe (Iron)	Max. 50 ppm

Cat. No.	Pk	Pack type
84522.320	2,5 l	Plastic bottle

Sodium hydroxide 50% in aqueous solution
TECHNICAL

Assay	47 to 51 %
-------	------------

Cat. No.	Pk	Pack type
28265.322	2,5 l	Plastic bottle
28265.366	5 l	Plastic bottle
28265.446	20 l	Plastic drum

Sodium hydroxide 50% (w/v) in aqueous
solution GPR RECTAPUR®

Assay (W/V)	48.0 to 50.5 %
-------------	----------------

Cat. No.	Pk	Pack type
191543M	1 l	Plastic bottle
191546P	5 l	Plastic container
19154CV	25 l	Plastic drum

Sodium hydroxide 35% in aqueous solution
GPR RECTAPUR®

Assay	34 to 36 %
Density (20/4)	1.370 to 1.390
Heavy metals (as Pb)	Max. 20 ppm
Cl (Chloride)	Max. 100 ppm
SO _x (Sulphate)	Max. 200 ppm
Fe (Iron)	Max. 20 ppm

Cat. No.	Pk	Pack type
28224.296	1 l	Plastic bottle
28224.365	5 l	Plastic bottle
28224.445	20 l	Plastic drum

Sodium hydroxide 35% in aqueous solution
TECHNICAL

Assay	Min. 34 %
Heavy metals (as Pb)	Max. 50 ppm
Fe (Iron)	Max. 50 ppm

Cat. No.	Pk	Pack type
28221.296	1 l	Plastic bottle
28221.365	5 l	Plastic bottle
28221.445	20 l	Plastic drum
28221.558	200 l	Plastic drum

Sodium hydroxide 32% in aqueous solution
AnalR NORMAPUR® analytical reagent, for
nitrogen analysis

Assay	Min. 32 %	Heavy metals (as Pb)	Max. 10 ppm
Total N (Nitrogen)	Max. 1 ppm	Cl (Chloride)	Max. 20 ppm
CO ₃ (as Na ₂ CO ₃)	Max. 1.0 %	SiO _x (as SiO ₂)	Max. 50 ppm
SO _x (Sulphate)	Max. 30 ppm	Al (Aluminium)	Max. 10 ppm
Fe (Iron)	Max. 10 ppm		

Cat. No.	Pk	Pack type
28225.290	1 l	Plastic bottle
28225.324	2,5 l	Plastic bottle
28225.360	5 l	Plastic bottle
28225.415	10 l	Plastic drum