



Environmentally friendly certified thermometers, Enviro-Safe®



Enviro-Safe® liquid

These thermometers are made with 100% non toxic, non hazardous, biodegradable liquid. Easy to read thanks to a high contrast green against white back.

- Lead free glass
- Individual serial numbers
- Accuracy without any of the hazards of mercury

Division: 1,0 °C

Traceable NIST/DKD. Compliant with Envirokleen™.

Delivery information: Supplied with a statement of accuracy in SafetyPak® recyclable packaging.

Range (°C)	Accuracy (°C)	Length (mm)	Immersion depth (mm)	Pk	Cat. No.
Partial immersion					
-10...+110	±1,0	200	50	1	620-0880
-10...+150	±1,0 (1,5>105)	200	50	1	620-0882
-20...+110	±1,0	305	76	1	620-0831
-20...+150	±1,0 (1,5>105)	305	76	1	620-0832
-10...+260	±1,0 (1,5>105)	355	76	1	620-0834
Total immersion					
-10...+110	±1,0	200	Plný	1	620-0881
-10...+150	±1,0 (1,5>105)	200	Plný	1	620-0883
-20...+110	±1,0	305	Plný	1	620-0836
-20...+150	±1,0 (1,5>105)	305	Plný	1	620-0835
-10...+225	±1,0 (1,5>105; 2,0>200)	355	Plný	1	620-0833



Environmentally friendly high contrast thermometers, Easy-Read®



Enviro-Safe® liquid

These thermometers are easy to read quickly and accurately due to the high contrast black numbering against a yellow background.

- Individual serial numbers - except pocket thermometers
- Eliminates reading errors
- Non toxic, non hazardous, biodegradable liquid

Traceable to NIST/DKD. Compliant with Envirokleen™.

Delivery information: Supplied in individually protected Safety-Pak® packaging with a statement of accuracy.

Range (°C)	Accuracy (°C)	Division (°C)	Length (mm)	Immersion depth (mm)	Pk	Cat. No.
Partial immersion						
-10...+150	±1,0	1,0	200	50	1	620-0781
-10...+110	±1,0	1,0	200	50	1	620-0783
-10...+260	±1,0 (1,5>105; 2,0>200)	1,0	355	76	1	620-0784
-20...+150	±1,0	1,0	305	76	1	620-0786
-20...+110	±1,0 (1,5>105)	1,0	305	76	1	620-0788
Total immersion models						
-10...+110	±1,0	1,0	200	Plný	1	620-0782
-10...+225	±1,0	1,0	355	Plný	1	620-0785
-20...+150	±1,0 (1,5>105)	1,0	305	Plný	1	620-0787
-20...+110	±1,0	1,0	305	Plný	1	620-0789
Pocket models						
-5...+50	±0,5	0,5	160	Total	1	620-0779
-10...+110	±1,0	1,0	160	Total	1	620-0780
-30...+50	±1,0	1,0	160	Total	1	620-0903